WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 9661
Rec. 19
Well No. .....
Permit No. .....
Do not fill in

Owner Joseph Hurst Driller W. E. Blain

Address 3415 Clark Dr. Washoe Farms Carson City Address Box 255 Carson City Lic. No. 301

Location of well: ¼ ¼ Sec. 31, T. 17 N/S, R. 20 E, in Washoe County

or

Water will be used for Domestic Total depth of well 75 ft

Size of drilled hole 10" to 50 ft Weight of casing per linear foot 9.7 lbs

Thickness of casing 10 ga Temp. of water Cold

Diameter and length of casing 6" x 76 ft 4 ft lengths
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 21 ft

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well 8-4-67 Date of completion of well 8-5-67

Type of well rig Cable Tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	3	3	Brown Sandy Topsoil
3	23	20	Yellow Sandy clay
23	28	5	Brown Sand
28	42	14	Yellow Sand
42	44	2	Blue Sandy clay
44	52	8	Brown Sand
52	54	2	Brown Sandy clay
54	61	7	Brown Sand
61	65	4	Blue Sandy clay
65	72	7	Brown Sand
72	75	3	Blue Clay

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 65 to 72 ft.

Other aquifers 23-28
44-52
54-61

First water at 23 feet.

Casing perforated

from 52 to 72 ft.

Size of perforations

3" x 3/32"

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6"	0	75	76	Cement to 50 ft

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Test by bailing — 20 G.P.M.

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed W. E. Blaser
Well Driller

By Clarence Blaser Co. Owner

License No. 201

Dated 8-25, 1967

(Not to be filled in by Driller)