WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 9763
Rec. Nov. 8 1967
Well No.
Permit No.
Do not fill in CARD

Owner: Lee Doss
Driller: W. E. Blair
Address: 12550 Westridge Drive Reno
Address: Box 255 Carson City Lic. No. 301
Location of well: S ½ ¼ Sec. 18, T. 18 N/S, R. 20 E, in Washoe County
or

Water will be used for: Domestic
Total depth of well: 127
Size of drilled hole: 12" to 50 ft
Weight of casing per linear foot: 12.5
Thickness of casing: 12 ga
Temp. of water: Cold
Diameter and length of casing: 8" X 128' (4 ft lengths)
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure
If nonflowing well give depth of standing water from surface: 100 ft
If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well: 10-9-67
Date of completion of well: 10-15-67
Type of well rig: Cable Tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	1	1	Brn Top Soil
1	4	3	Brn. Hard pan
4	52	48	Brown Cemented Rocks
52	64	8	Brown Cemented gravel
64	80	16	Brown " Rocks
80	90	10	" " Gravel
90	104	14	" " Rocks
104	116	12	" " Gravel
116	127	11	Brown Sand & Gravel

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 120 to 127 ft.

Other aquifers

First water at 120 feet.

Casing perforated
from 108 to 128 ft.

Size of perforations
3" X 3/32"

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
8"	0	127	128	Sealed to 50 ft with cement

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Test by bailing - 32 G.P.M.

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed W. E. Blair
Well Driller

By Florence Blair Co-Owner

License No. 301

Dated 11-6, 1967

(Not to be filled in by Driller)