21690

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 10067
Rec. May 27 1968
Well No.
Permit No.
Do not fill in

Owner Lincoln D. Dempsey Driller Howard Turley

Address Dixie Rte Fallon Nev Address Dixie Rte Fallon Nev Lic. No. 537

Location of well: SW ¼ NE ¼ Sec. 8, T 21 N/S, R 35 E, in Churchill County

or

Water will be used for irrigation Total depth of well 210

Size of drilled hole 18" Weight of casing per linear foot 42

Thickness of casing 1/4" Temp. of water 60°

Diameter and length of casing 16 1/2" 210'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure 30 GPM.

If nonflowing well give depth of standing water from surface

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well May 17 1968 Date of completion of well May 24 1968

Type of well rig Rotary

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	10	10	Loam
10	80	70	Sand & Gravel
80	105	25	Clay
105	155	50	Gravel & Coarse Sand
155	180	25	Hard Pan.
180	200	20	Clay
200	210	10	Gravel

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 105 to 155 ft.

Other aquifers 200 - 210

Also 10 - 80 ft.

First water at 10 feet.

Casing perforated

from 105 to 155 ft.

200 - 210

Size of perforations

1/4" x 4"

(OVER)

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Howard Lindley
Well Driller

By

License No. 537

Dated May 25, 19 68

(Not to be filled in by Driller)