

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 10149  
 Rec. July 1968  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Do not fill in. ARD

Owner Ray Mills Driller Marcia Drilling  
 Address Ponderosa Dr. Carson City, Nev. Address Carson City, Nev. Lic. No. 7988  
 Location of well: NE 1/4 SW 1/4 <sup>MIDLINE</sup> Sec. 13.2, T. 15 N/S, R. 20 E, in Owens County  
 Permit No. \_\_\_\_\_  
 Water will be used for Domestic Total depth of well 153 feet  
 Size of drilled hole 6 inch Weight of casing per linear foot 13#  
 Thickness of casing .188 wall Temp. of water Cold  
 Diameter and length of casing 6 1/2 X 1000 153 feet  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure Not flowing  
 If nonflowing well give depth of standing water from surface 60 feet  
 If flowing well describe control works Not flowing  
(Type and size of valve, etc.)  
 Date of commencement of well 3-1-68 Date of completion of well 3-15-68  
 Type of well rig Cable tool

## LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, etc.
1	45	45	Cemented Sand	
45	50	5	1st Water - Gravel	Chief aquifer (water-bearing formation)
50	95	45	Cemented Sand	
95	105	10	2d Water	from <u>45</u> to <u>50</u> ft.
105	120	15	Clay	
120	136	16	Cemented Sand	Other aquifers. <u>95 - 105</u>
136	152	16	3rd Water - Cemented gravel	<u>136 - 152</u>
152	153	1	<del>Gravel</del> Gravel	
				First water at <u>45</u> feet.
				Casing perforated
				from <u>148</u> to <u>120</u> ft.
				Size of perforations
				<u>1/8 " X 6 "</u>
				<u>Torch perfor</u>

