

**WELL LOG AND REPORT TO THE STATE ENGINEER
OF NEVADA**

Log No. 10160
 Rec. 7-19 1968
 Well No. _____
 Permit No. 23289

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Do not fill in.

Owner Frank E. and Helen S. Spinner Driller Pete Anderson
 Address P.O. Box 56, Steamboat Nevada Address 3680 Churchill Dr
 Location of well: $\frac{1}{4}$ Sec. 31, T. 17 N/S, R. 20 E, in Washoe County

Water will be used for Domestic Total depth of well 140'

Size of drilled hole 6" Weight of casing per linear foot 13 lbs.

Thickness of casing 3/16" or 188 Temp. of water Cool

Diameter and length of casing 6" - 100' - 5" - 96' - 140'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure. ✓

If nonflowing well give depth of standing water from surface. 21'

If flowing well describe control works. ✓
(Type and size of valve, etc.)

Date of commencement of well August 17, 66 Date of completion of well August 24, 66

Type of well rig Cable Tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	3	3'	loose sand
3	24	21'	Coarse sand
24	38	14"	Sandy clay
38	52	14	fine sand
52	60	8'	Sandy clay
60	72	12'	Coarse sand & gravel
72	86	14	Coarse & fine sand
86	98	12	Coarse sand & gravel
98	100	2	Clay
100	140	40	Semi hard granite
140	0	0	very hard granite

Water-bearing Formation, Casing Perforations, etc.

Chief aquifer (water-bearing formation)
 from 86' to 98' ft.

Other aquifers 60' - 72'

First water at 21' feet.

Casing perforated
 from 76' to 140' ft.

Size of perforations
1/8" x 1/4" Touch cut

