Log No. 10279
Rec. Oct 16 1968
Well No.
Permit No. CARD
Do not fill in.

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner: Ed Dennick
Driller: Pete Anderson
Address: 301 Montello Reno, Nev.
Address: 3680 Churchill Dr Carson City, Nev
Lic. No. 307

Location of well: ¼ ¼ Sec. 5, T. 16 N/S, R. 20 E, in Washoe County
or New Washoe City Sub. 5

Water will be used for: Domestic
Total depth of well: 125'

Size of drilled hole: 6"
Weight of casing per linear foot: 13 lbs

Thickness of casing: 3/16"
Temp. of water: Cool

Diameter and length of casing: 6" 120'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure: -

If nonflowing well give depth of standing water from surface: 70'

If flowing well describe control works: -
(Type and size of valve, etc.)

Date of commencement of well: Sept 1-68
Date of completion of well: Sept 10, 68

Type of well rig: Cable Tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	10	10'	loose Sand
10'	60	50	Decomposed Sand
60	70	10	Sandy Clay
70	96	26	Sand + Gravel
96	110	24	Brown Clay
110	120	10	Sand + Gravel
120	125	5	Clay

(OVER)

Water-bearing Formation, Casing Perforations, etc.

Chief aquifer (water-bearing formation)
from 110 to 120 ft.
Other aquifers 70 - 96

First water at 70 feet.

Casing perforated
from 100' to 120 ft.

Size of perforations
1/8 X 4"

919