

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 10291  
 Rec. 10-24 1968  
 Well No. ....  
 Permit No. ....

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Do not fill in.

Owner F. R. Baxter Driller F. R. Baxter  
 Address P. O. Box 744, Carson City, Nev. Address Box 744 Carson City Lic. No. 457  
 Location of well: NW 1/4 NE 1/4 Sec. 23, T. 15 N/S, R. 20 E, in Ormsby County  
 or 1229 Deer Run 23cebbd  
 Water will be used for Domestic Total depth of well 160 ft.  
 Size of drilled hole ten inch Weight of casing per linear foot .....  
 Thickness of casing 10 gage Temp. of water wa. rm  
 Diameter and length of casing 6 inch 20 ft. full length of well  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure .....  
 If nonflowing well give depth of standing water from surface 120 ft.  
 If flowing well describe control works .....  
(Type and size of valve, etc.)  
 Date of commencement of well Oct., 8, 1968 Date of completion of well Oct., 11 1968  
 Type of well rig Davy 2000 Rotary

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, etc.
0	20		sand	
20	40	10 ft.	boulders and clay	Chief aquifer (water-bearing formation)
40	60	20 ft.	Clay and streaks of gravel	from ..... to ..... ft.
60	80	20 ft.	broken formation and streaks of black sand and gravel.	Other aquifers.....
80	110	30 ft.	conglomerate streaks of sand and gravel	
110	130	20 ft.	same as above.	
130	150	20 ft.	yellow clay with streaks of gray coarse sand.	
150	160	10 ft.	coarse sand.	
				First water at <u>145</u> feet.
				Casing perforated from <u>140</u> to <u>160</u> ft.
				Size of perforations <u>factory slotted</u>