

**WELL LOG AND REPORT TO THE STATE  
ENGINEER OF NEVADA**  
(Economic Development Administration)

Log No. 10404  
 Rec. Jan 23 19 69  
 Well No. ....  
 Permit No. 8888  
*Do not fill in*

Owner Lake Pyramid Paiute Tribal Council Driller Western Well Drilling Co., Ltd.  
Wadsworth Industrial Park P.O. Box 47  
 Address Wadsworth, Nevada Address San Jose, California 95103 Lic. No. 8758

Location of well:  $\frac{1}{4}$   $\frac{1}{4}$  Sec. ...., T. .... N/S, R. .... E, in Washoe County  
 or 3000' N. of Wadsworth on Hwy 34- and 700' E. of Hwy 34 - 2 miles N.W. of Wadsworth

Water will be used for industrial-municipal Total depth of well 470'

Size of drilled hole 25" Weight of casing per linear foot 14" - 38#  
10-3/4" - 28#

Thickness of casing .250 Temp. of water .....

Diameter and length of casing 50' - 26" x .250; 250' - 14" x .250; 213' - 10-3/4" x .250  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure .....

If nonflowing well give depth of standing water from surface 94'

If flowing well describe control works .....

(Type and size of valve, etc.)

Date of commencement of well September 18, 1968 Date of completion of well November 7, 1968

Type of well rig Hydraulic Rotary

**LOG OF FORMATIONS**

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
0	3	3	Loose Sand	
3	10	7	Gravel with Silt & Sand	
10	23	13	Medium Sand & Small Gravel	
23	45	22	Sand & Gravel	
45	80	35	Sand with Gravel Stringers	
80	90	10	Sand & Gravel with Grey Clay Stringers	
90	92	2	Sand with Gravel & Grey Clay Stringers	
92	101	9	Medium Gravel with Silty Sand Stringers	
101	112	11	Sand with Tight Gravel Stringers	
112	137	25	Gravel (Tight and Hard)	
137	148	11	Sand with Tight Gravel Stringers &	
148	155	7	Grey Sandy Clay (Grey Clay Stringers)	
155	158	3	Grey Clay	
158	166	8	Medium Sand & Gravel	
166	179	13	Blue Clay	
179	230	51	Medium to Large Gravel with Hard Hard Streaks of Quartz	
230	270	40	Medium to Large Gravel with Hard Streaks	
270	305	35	Sand & Gravel with Hard Streaks	
305	317	12	" " " " " "	
317	327	10	Sand & Gravel with Brown Clay Stringers & Hard Streaks	

  

Chief aquifer (water-bearing formation)	
from	to
230	270
Other aquifers	
270 - 295	
305 - 315	
355 - 380	
390 - 395	
400 - 405	
410 - 420	
430 - 455	

  

First water at	feet.
240 ft. to 250 ft.	ft.
252	- 295
305	- 315
355	- 380
390	- 395
400	- 405
410	- 420
430	- 455

LOG OF FORMATIONS—Continued

From feet	To feet	Thickness	Type of material
327	340	13	Cemented Sand & Gravel (Very Hard)
340	345	5	Hard Cemented Sand & Gravel
345	356	11	Brown Sandy Clay (Dry)
356	365	9	Medium Grey Sand
365	372	7	Hard Cemented Sand & Gravel
372	375	3	Brown Sticky Clay
375	385	10	Sand & Gravel (Tight)
385	470	85	Brown Clay Stringers

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
14"	0	250	250	
10-3/4"	252	465	213	
26"	0	50	50	Conductor Casing in 34" Bore

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Maximum Capacity - 1200 G.P.M.

Water Analysis - See Sharp, Krater & Associates, 2167 East Second St., Reno, Nevada

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed WESTERN WELL DRILLING CO., LTD.  
Well Driller

By J. F. Guardino  
J. F. Guardino, President  
License No. 8758

Dated January 21, 1969

(Not to be filled in by Driller)

.....  
 .....  
 .....  
 .....  
 .....  
 .....  
 .....  
 .....  
 .....  
 .....

1969 JAN 23 AM 9 59  
 OFFICE  
 ST. ENGINEER