

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 10679  
 Rec. \_\_\_\_\_ 19\_\_\_\_  
 Well No. \_\_\_\_\_  
 Permit No. Washoe Vall  
*Do not fill in Card*

Owner D. I. Mustard Driller Marcin Drilling Co.

Address Lion Dr. Washoe City Address 4340 Hwy 50E Lic. No. 360

Location of well:  $\frac{1}{4}$  SW  $\frac{1}{4}$  Sec. 6, T. 16 N/S, R. 20 E, in Washoe County

Water will be used for Domestic Total depth of well 145 feet

Size of drilled hole 6 inch Weight of casing per linear foot 13#

Thickness of casing .188 Temp. of water Cold

Diameter and length of casing 6" X 145 feet  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure Not flowing

If nonflowing well give depth of standing water from surface \_\_\_\_\_

If flowing well describe control works Not flowing  
(Type and size of valve, etc.)

Date of commencement of well 6-4-69 Date of completion of well 6-27-69

Type of well rig Cable

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
1	65	65	Quick sand
65	70	5	Quick sand
70	73	3	1st water
73	85	12	Quick sand
85	120	25	Bluish sand
120	125	5	2d water
125	132	7	Sand
132	145	13	Snotty Sand and clay

Water-bearing Formation, Casing Perforations, Etc.

---

Chief aquifer (water-bearing formation)  
 from 70 to 73 ft.  
 Other aquifers 120 to 125

---

First water at 70 feet.

Casing perforated  
 from 116 to 140 ft.

Size of perforations  
**Torch 6" X 1/8"**

