log sent to CC per [illegible] request 9-29-69

Log No. 10774
Rec. ... 19...
Well No. ...
Permit No. ...
Do not fill in

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

(Now Raymond Martin)

Owner: Mrs. Bela Havas  Driller: S. R. McKinney & Son

Address: 2210 Santa Paula Drive, Las Vegas  Address: 1042 S. Main Las Vegas  Lic. No. 45

Location of well: NE ¼ SW ¼ Sec. 19, T. 21 N/S, R. 62 E, in Clark County

or South ½ of SE ¼ of NE ¼ of SW ¼ of Section 19, Twp. 21, Range 62 E.

Water will be used for: Domestic  Total depth of well: 160 ft.

Size of drilled hole: 12" to 50 ft, 10" to 160  Weight of casing per linear foot: 26 lb.

Thickness of casing: 1/4"  Temp. of water:

Diameter and length of casing: 8" I.D. to 160 ft.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure:

If nonflowing well give depth of standing water from surface: Surface

If flowing well describe control works:
(Type and size of valve, etc.)

Date of commencement of well: Feb. 14, 1955  Date of completion of well: Feb. 15, 1955

Type of well rig: Bucyrus Erie 24 L. Spudder

## LOG OF FORMATIONS

| From feet | To feet | Thickness feet | Type of material |
|---|---|---|---|
| 0 | 4 | 4 | sand |
| 4 | 41 | 37 | red clay |
| 41 | 44 | 3 | sandstone |
| 44 | 48 | 4 | red clay |
| 48 | 51 | 3 | sandstone water |
| 51 | 54 | 3 | red clay |
| 54 | 58 | 4 | red sand water |
| 58 | 69 | 11 | red clay |
| 69 | 72 | 3 | red sand water |
| 72 | 76 | 4 | sandstone |
| 76 | 84 | 8 | red clay |
| 84 | 87 | 3 | red sand water |
| 87 | 99 | 12 | red clay |
| 99 | 102 | 3 | red sand water |
| 102 | 106 | 4 | sandstone water |
| 106 | 123 | 17 | red clay |
| 123 | 130 | 7 | sandstone water |
| 130 | 134 | 4 | red sand water |
| 134 | 139 | 5 | red clay |
| 139 | 143 | 4 | sandstone water |
| 143 | 146 | 3 | red sand water |
| 146 | 149 | 3 | red clay |
| 149 | 152 | 3 | sandstone water |
| 152 | 160 | 8 | red clay |

(OVER)

Water bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 149 to 152

Other aquifers
139 to 146
123 to 134, 9[illegible] to 100

Static water 48 feet.

Casing perforated
from 90 to 160

Size perforations
3/16" x 10"

LOG OF FORMATIONS—*Continued*

| From feet | To feet | Thickness | Type of material |
|---|---|---|---|
| | | | |

CASING RECORD

| Diam. casing | From feet | To feet | Length | "Remarks"—Seals, Grouting, Etc. |
|---|---|---|---|---|
| 8" I.D. | 0 | 160 | 160 | 8" I.D. XXXXX Casing cemented down to 50 ft. with 1½ yds. concrete. |

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc

Well flows approx. 3 G.P.M.
Bailed 60 G.P.M. from 45 ft.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed [illegible] Well Driller

By [illegible]

License No. 45

Feb 28, 19 55

(Not to be filled in by Driller)