WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 100655
Permit No.
Basin 230

NOTICE OF INTENT NO. 29871

1. OWNER Palm Harbor Homes
MAILING ADDRESS 583 S. HWY 160 Pahrump, Nv. 89048
ADDRESS AT WELL LOCATION 109 N. Pueblo Amargosa Valley, Nv 89020

2. LOCATION NE ¼ SE ¼ Sec. 22 T. 16 N/S R. 49 E. NYE County
PERMIT NO. (Issued by Water Resources) Parcel No. 19-541-73 Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVD
☐ Air ☒ Other Mud

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
gravel w/ snd.		0	130	130
gravel	1st	130	145	15
limestone w/white cly. layers		145	125	30
gravel w/ snd.	2nd	175	190	15
Sndy. tan cly.		190	215	25
limestone		215	220	5
Bottom of Well			220	

DCNR/DWR RECEIVED
AUG 22 2006
LAS VEGAS OFFICE

Date started 8/4, 2006
Date completed 8/10, 2006

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 220 Feet Depth Cased 220 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
12¼ Inches		0 Feet	220 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6	PVC		0	220
Surface Protective Casing				
8	Steel	.188	0	5

Perforations:
Type perforation Machined
Size perforation ⅛" x 3" every 12"
From 140 feet to 180 feet
From 200 feet to 210 feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50'
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☐ Neat Cement ☐ Cement Grout ☒ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 50 feet to 220 feet

9. WATER LEVEL
Static water level 137 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature Cool °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Cook Drilling Co. (Contractor)
Address H.C. 70 Box 543 Amargosa Valley, Nv. 89020 (Contractor)
Nevada contractor's license number issued by the State Contractor's Board 5376-A
Nevada driller's license number issued by the Division of Water Resources, the on site driller 2160
Signed (By driller performing actual drilling on site or contractor)
Date 8/10/06

(Rev. 12-01) USE ADDITIONAL SHEETS IF NECESSARY (O)-627