WHITE - DIVISION OF WATER RESOURCES
CANARY - CLIENT'S COPY
PINK - WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 100916
Permit No.
Basin 092B

NOTICE OF INTENT NO. 57812

1. OWNER Harry Shepherd
MAILING ADDRESS 5235 Goldenrod
Reno, NV 89511

ADDRESS AT WELL LOCATION 11780 Overland Rd.
Lemmon Valley

2. LOCATION SE 1/4 NW 1/4 Sec. 15 T 21N N/S R 19E E Washoe County
PERMIT NO. (Issued by Water Resources) | Parcel No. 080-383-14 | Subdivision Name

3. WORK PERFORMED
☐ New Well ☐ Replace ☐ Recondition
☐ Deepen ☒ Abandon ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
On this date we abandoned a 8" x 100' well with a				
6" liner from 90' to 130' and a 4" liner from 96'				
to 196' perforating from 60' to 50' at 50' a				
sanitation seal was found. We then poured 3.25				
cubic yards of neat cement mixed 5.2 gallons of				
water per sack into the well filling it to the				
surface. We then cut off the top 2' of casing all				
per Tom Gallagher instructions.				
NAD 83				
N 39.68882				
W 119.83824				
Washoe County Permit # WL 060168				

Date started 9/7/2006, 19__
Date completed 9/7/2006, 19__

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 196 Feet Depth Cased 196 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
Inches	Feet	Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
8 5/8	16.94	.188	0	100
6 5/8	12.92	.188	90	130
4 1/2	8.66	.188	96	196

Perforations:
Type perforation Factory & Mills Knife
Size perforation 1/8 x 3 & Puncture
From 60 feet to 130 feet
From 154 feet to 196 feet
From 60 feet to 50 feet
From feet to feet
From feet to feet

Surface Seal: ☐ Yes ☒ No
Depth of Seal
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout
Gravel Packed: ☐ Yes ☒ No
From feet to feet

9. WATER LEVEL
Static water level 188 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Bruce MacKay Pump & Well Service, Inc. (Contractor)
Address 1600 Mt. Rose Hwy (Contractor)
Reno, NV 89511
Nevada contractor's license number issued by the State Contractor's Board 23096
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2299
Signed R. Bruce MacKay
By driller performing actual drilling on-site or contractor
Date 9/7/2006

USE ADDITIONAL SHEETS IF NECESSARY