WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 101342
Permit No.
Basin 084

NOTICE OF INTENT NO. 56450

1. OWNER Palomino Valley Ass.
MAILING ADDRESS 1475 Terminal Way Ste. A5-5 Reno NV, 89502-3209
ADDRESS AT WELL LOCATION West of Sage Flats Rd, Warm Springs.

2. LOCATION NE ¼ NW ¼ Sec. 5 T. 22N N/S R. 21E E. Washoe County
PERMIT NO. M10-1392 (Issued by Water Resources) 00709013 (Parcel No.) Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☐ Other Auger

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Brown Silt		0	3	3
Brown Silty Sand		3	15	12
Brown Silt		15	17	2
Brown Silty Sand		17	25	8
Brown Silt		25	27	2
Brown Silty Sand		27	37	10
Brown Lean Clay		37	43	6
Dark Brown Silty Sand		43	58	15
Dark Brown Lean Clay		58	61	3
Brown Clayey Sand		61	64	3
Dark Brown Lean Clay	106	64	130	66
Brown Clayey Sand	106	130	132	2
Brown, Grey Lean Clay		132	152	20
Grey Silty Sand	153	152	156	4
Brown, Grey Lean Clay		156	158	2
Grey, Brown Silty Sand		158	165	7

Date started Dec 14, 2005
Date completed Dec 15, 2005

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 165 Feet Depth Cased 165 Feet

HOLE DIAMETER (BIT SIZE)

Inches	From (Feet)	To (Feet)
8	0	165

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2 PVC	PVC	Sch 40	0	145
8 PVC	PVC	Sch 40 Slotted	145	165

Perforations:
Type perforation mill
Size perforation 0.20
From 145 feet to 165 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 141
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☐ Neat Cement ☒ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 143 feet to 165 feet

9. WATER LEVEL
Static water level Dry feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature 60.0 °F Quality clear

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name WDC Exploration + Wells (Contractor)
Address 9580 County Rd (Contractor)
930 Zamora, CA 95698
Nevada contractor's license number issued by the State Contractor's Board 0012852
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M-2263
Signed [signature] (By driller performing actual drilling on site or contractor)
Date 12-15-2005

(Rev. 12-01) USE ADDITIONAL SHEETS IF NECESSARY (O)-627