


STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT



OFFICE USE ONLY

Log No. 101574
Permit No. _____
Basin 066

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in
accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 57016

1. OWNER Neosmart Mining Corp ADDRESS AT WELL LOCATION Twin Creeks mine
MAILING ADDRESS PO box 69 Golconda NV 89414 Hydrology Dept. 30 miles north of Golconda NV
Subdivision Name: _____ County: Humboldt

2. LOCATION NW 1/4 NE 1/4 Sec 18 T 39 N R 43 E Latitude _____ UTM E 1593751.41 NAD 27
PERMIT/WAIVER No. _____ Longitude _____ N 14987007.90 NAD 83/WGS 84

Issued by Water Resources Parcel No. _____

3. WORKED PERFORMED
 New Well Replace Recondition
 Deepen Other

4. PROPOSED USE
 Domestic Irrigation Test Cable Rotary RVC
 Municipal/Industrial Monitor Stock Air Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
<u>m/o 18-16B</u>				
<u>First H2O @ 1300'</u>	<u>S-</u>	<u>10 gpm</u>		
<u>1380 - 15 gpm</u>				
<u>1440 20 gpm</u>				
<u>1500 30 gpm</u>				
<u>1660 43 gpm</u>				
<u>1740 60 gpm</u>				
<u>Static @ 1054'</u>				
<u>Trimmy in 69 Ft³ of 1/4" gravel</u>				
<u>from 1780 - 1430'</u>				
<u>Place 3/8 Hole plug 1430 to 50</u>				
<u>282 Ft³</u>				
<u>Cement top 50'</u>				
<u>Develop well through trimmy</u>				
<u>with water pumping while</u>				
<u>moving through screened area</u>				
<u>of well. Use 10,000 gallons H2O</u>				
<u>weld monument on and pour cement pad</u>				

9. WELL CONSTRUCTION

Depth Drilled 1780 Feet Depth Cased 1777 Feet

HOLE DIAMETER (BIT SIZE)

Inches	From	To	Feet	Feet
<u>1 3/4</u>	<u>0</u>	<u>20</u>		
<u>6 1/2</u>	<u>20</u>	<u>1360</u>		
<u>6 7/8</u>	<u>1360</u>	<u>1780</u>		

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
<u>2 3/8</u>	<u>5 Pf</u>	<u>Sch 40</u>	<u>-1777</u>	<u>+3</u>

Perforations:

Type of perforation Slot

Size of perforation 1/8"

From	feet to	feet	feet
<u>1737</u>		<u>1437</u>	

Annular Seal: Yes No

<input type="checkbox"/> Neat Cement	<u>50</u> to <u>0</u>	<input type="checkbox"/> Pumped	<input checked="" type="checkbox"/> Poured
<input type="checkbox"/> Cement Grout	_____ to _____	<input type="checkbox"/> Pumped	<input type="checkbox"/> Poured
<input type="checkbox"/> Concrete Grout	_____ to _____	<input type="checkbox"/> Pumped	<input type="checkbox"/> Poured
<input type="checkbox"/> ≥30% Bentonite Grout	_____ to _____	<input type="checkbox"/> Pumped	<input type="checkbox"/> Poured

Gravel Pack: Yes No 178 to 1430 Pumped Poured

Type: 1/4 gravel - trimmy in

Bentonite Chips: Yes No 1430 to 50 Pumped Poured

Type: 3/8" kwik plug

Date started: 6/15 .20 06
Date completed: 7/2 .20 06

7. Water Level

Static water level: 1054' feet below land surface
Artesian Flow: _____ G.P.M. _____ P.S.I.
Water Temperature: _____ °F
Quality: good

8. WELL TEST DATA

TEST METHOD:	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailer <input checked="" type="checkbox"/> Pump <input type="checkbox"/> Air Lift			
<u>Injection</u>	<u>100</u>	<u>13' Rise in static level</u>	
<u>while injection</u>			

10. DRILLER'S CERTIFICATION

This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Eklund Drilling Co Contractor
Address P.O. Box 2748 Contractor
Eiko, NV 89803 Contractor

Nevada contractor's license number 0030823
issued by the State Contractor's Board

Nevada driller's license number issued by the Division of Water Resources, the on-site driller M 2089

Signed D. Skl By driller performing actual drilling on site or contractor
Date 7/2/06

(Rev 05-06)

USE ADDITIONAL SHEETS IF NECESSARY

STATE ENGINEERS OFFICE

2006 AUG 31 AM 11:06

RECEIVED