39° 30.213 N 118° 52.162 W

WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

I

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 102509
Permit No.
Basin 101

NOTICE OF INTENT NO. 56184

1. OWNER CSE Baldon
MAILING ADDRESS
ADDRESS AT WELL LOCATION ~~5000 Skyridge~~ 2000 Skyridge
Skyridge, Dillon

2. LOCATION ~~NW~~ NE ¼ NW ¼ Sec. 20 T. 19 N/S R. 28 E. Churchill County
PERMIT NO. 8-175-22
Issued by Water Resources | Parcel No. | Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Sand		1	5	
Clay		15	37	
Coarse Sand		37	42	
Coarse Gravels		42	51	
Black/Grey Clay & Sand		51	61	
Coarse Black Sands		61	70	
Black Clay		70	76	
Coarse Black Sand & Clay		76	95	
Blong Clay, Sands & Gravels		95	98	
Blonde Clay		98	102	
Coarse Sands Blonde		102	112	
Clay & Gravels		112	119	
Clay 118-119				
39.503550 N				
118.869367 W NAD83				

Date started 10/26/06, 20
Date complated 10/26/06, 20

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
45		3½ hrs

8. WELL CONSTRUCTION
Depth Drilled 120 Feet Depth Cased 120' Feet

HOLE DIAMETER (BIT SIZE)

	From	To
10 5/8 Inches	1 Feet	120' Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8	13.	1.88	1	20
6 5/8	PVC	SH 40	20	120

Perforations:
Type perforation Machine Perf
Size perforation 1/8 x 4 x 5# perf
From 100 feet to 110' feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 20'
Placement Method: ☐ Pumped ☐ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 50 feet to 120' feet

9. WATER LEVEL
Static water level 29. feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature C °F Quality Good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Leach Drilling Inc
Contractor
Address PO 593
Contractor
S.S. NV 89429
Nevada contractor's license number issued by the State Contractor's Board 0031841
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1836
Signed [signature]
By driller performing actual drilling on site or contractor
Date 10/26/06

(Rev. 12-01) USE ADDITIONAL SHEETS IF NECESSARY (O)-627