WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 102894
Permit No.
Basin 117

NOTICE OF INTENT NO. 30442

1. OWNER Lynn Halpin
MAILING ADDRESS Box 542
Dyer, NV 89010

ADDRESS AT WELL LOCATION South side of Swanger Circle Lot # 20
Dyer, NV 89010

2. LOCATION NW ¼ NW ¼ Sec. 22 T. 4 N R. 36 E Esmeralda County
PERMIT NO. Issued by Water Resources | Parcel No. 007-641-01 | Mt. Mt. White Mountain Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Clay & small rocks		0	22	22
Rocks BW Tan clay		22	30	8
Rocks sand & clay		30	105	75
Brown clay & gravel		105	126	21
Rocks		126	127	1
Clay & Gravel		127	160	33
Brown clay & w. sand		160	200	40
Tan clay & gravel		200	255	55
Sandy clay		255	280	25
Gravel sand & clay		280	307	17
Clay		307	318	11
Gravel & some clay		318	320	2
World Geodetic System 1984 used				
37° 34.798	N			
117° 58.312	W			
Elevation 4,943				

Date started 4-11-07, 20
Date completed 4-17-07, 20

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
100+	300	2
75	200	2
42	150	1
20	125	2

8. WELL CONSTRUCTION
Depth Drilled 320 Feet Depth Cased 310 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
9 7/8 Inches	0 Feet	320 Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8	steel	.188	+1	10
6 5/8			10	310

Perforations:
Type perforation saw cut horizontal
Size perforation
From 170 feet to 310 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: X Yes No
Depth of Seal 50
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☐ Neat Cement ☒ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 50 feet to 320 feet

9. WATER LEVEL
Static water level 93 feet below land surface
Artesian flow 0 G.P.M. 0 P.S.I.
Water temperature cool °F Quality good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Maranatha Drilling & Pump Service (Contractor)
Address 22893 HWY 6 (Contractor)
Benton CA. 93512
Nevada contractor's license number issued by the State Contractor's Board 039576
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1238
Signed Russell [illegible] (By driller performing actual drilling on site or contractor)
Date 5-7-07

(Rev. 12-02)

USE ADDITIONAL SHEETS IF NECESSARY

(01-612)