


LK-35

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT



OFFICE USE ONLY
Log No. 103011
Permit No.
Basin 857

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 59266

1 OWNER Newmont Mining Corp.
MAILING ADDRESS P.O. Box 669
Carlin, NV 89822

ADDRESS AT WELL LOCATION Gold Quarry Minesite, about 6 miles north of Carlin, NV

Subdivision Name: County: Eureka

2 LOCATION SE 1/4 SE 1/4 Sec 35 T 34N N/S R 51 E
PERMIT/WAIVER No. 56836
Issued by Water Resources Parcel No.

Latitude 40.783975 UTM E 567170 NAD 27
Longitude 116.203941 N 4514870 NAD 83/WGS 84

3 TYPE OF WELL
Domestic Irrigation Test
Municipal/Industrial Monitor Stock

Is this well being plugged because a replacement well was drilled? No
If yes, what is replacement well NOI?

Is there an existing well log? Yes
If yes, what is NDWR well log #? 71458

4 EXISTING WELL CONSTRUCTION
Depth Drilled 320 Feet Depth Cased 320 Feet

7 WELL PLUGGING PROCEDURE
Was well cleaned out to total depth? yes [X] no

Table with columns: Size O.D. (Inches), Weight/Ft. (Pounds), Wall Thickness (Inches), From (Feet), To (Feet). Row 1: 8.625, 32, 0.3, +2, 320

If well was not cleaned out to total depth, please explain why: Pumping equipment was pulled, and the well found to be open to original t.d.

Existing Perforations table with columns: Type of perforation, Size of perforation, From, To

Was the well contaminated? yes [X] no
Was the casing pulled? yes [X] no
Was the casing over drilled? yes [X] no

Additional Perforations table with columns: Type of perforator used, From, To, Number of perfs per linear foot

5 WATER LEVEL
Static water level 245 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature 60 °F Quality Good

8 WELL PLUGGING MATERIALS

6 Additional Notes or Comments
Abandonment procedure was discussed with DWR prior to performing the work. The basic procedure entails circulating the bentonite grout (Super Plug) until it will rise no further, then a bentonite chip (Kwik Plug) bridge. Neat cement is then pumped until it is 20' above the uppermost perforation in the casing. The balance of the casing is filled with clean fill or gravel, as a safety measure.

Material Used table with columns: From, To, Material, Pumped, Poured

Neat Cement Fluid Weight 15 lbs/gal
Bentonite Grout 12 % bentonite

Date Started 1/12/2007
Date Completed 1/13/2007

7 SIGNATURE AND DATE
Signature: [Handwritten Signature]
Date: 3/7/2007

9 DRILLER'S CERTIFICATION

This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.

Name Eklund Drilling Company, Inc. Contractor

Address PO Box 2748 Contractor
Elko, NV 89803

Nevada contractor's license number issued by the State Contractor's Board 0030823

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1776

Signed [Handwritten Signature]
By driller performing actual drilling on site or contractor

Date 3/7/2007