



STATE OF NEVADA DIVISION OF WATER RESOURCES <b>WELL DRILLER'S REPORT</b>		OFFICE USE ONLY																																																																																																			
		Log No.	10338																																																																																																		
		Permit No.																																																																																																			
		Basin	212																																																																																																		
Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340																																																																																																					
1. OWNER Clark County Aviation		NOTICE OF INTENT NO. 31425																																																																																																			
MAILING ADDRESS P.O. Box 11005 Las Vegas, Nv		ADDRESS AT WELL LOCATION McCarren Airport Terminal 3 5757 Wayne Newton Boulevard, Las Vegas, NV																																																																																																			
2. LOCATION <u>W 1/4 NW 1/4</u> 1/4 Sec <u>35</u> T <u>21</u> S R <u>61</u> E		Subdivision Name: County: <u>CLARK</u>																																																																																																			
PERMIT/WAIVER No. DW-1244A 162-35-101-018		Latitude UTM E NAD 27 Longitude N x NAD 83/WGS 84																																																																																																			
3. WORKED PERFORMED		4. PROPOSED USE <u>Dewater</u>																																																																																																			
<input checked="" type="checkbox"/> New Well <input type="checkbox"/> Replace <input type="checkbox"/> Recondition <input type="checkbox"/> Deepen <input checked="" type="checkbox"/> Other <input type="checkbox"/> Dewatering Well		5. WELL TYPE <input type="checkbox"/> Domestic <input type="checkbox"/> Irrigation <input type="checkbox"/> Test <input type="checkbox"/> Cable <input type="checkbox"/> Rotary <input type="checkbox"/> RVC <input type="checkbox"/> Municipal/Industrial <input type="checkbox"/> Monitor <input type="checkbox"/> Stock <input type="checkbox"/> Air <input checked="" type="checkbox"/> Other <input type="checkbox"/> Auger Bucket																																																																																																			
6. LITHOLOGIC LOG		9. WELL CONSTRUCTION																																																																																																			
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>Material</th> <th>Water Strata</th> <th>From</th> <th>To</th> <th>Thickness</th> </tr> </thead> <tbody> <tr> <td colspan="5"><b>Well # 7434</b></td> </tr> <tr> <td colspan="5">N486497.7 E632963</td> </tr> <tr> <td>Fill - gravelly clay</td> <td></td> <td>0</td> <td>8</td> <td>8</td> </tr> <tr> <td>Sandy lean clay</td> <td></td> <td>8</td> <td>14</td> <td>6</td> </tr> <tr> <td>Caliche - hard off white</td> <td></td> <td>14</td> <td>17</td> <td>3</td> </tr> <tr> <td>Sandy lean clay</td> <td></td> <td>17</td> <td>20</td> <td>3</td> </tr> <tr> <td>Fat Clay - w/gravels</td> <td></td> <td>20</td> <td>48</td> <td>28</td> </tr> <tr> <td>Caliche - hard off white</td> <td></td> <td>48</td> <td>52</td> <td>4</td> </tr> <tr> <td>Fat Clay - w/gravels partially cem</td> <td></td> <td>52</td> <td>61</td> <td>9</td> </tr> </tbody> </table>		Material	Water Strata	From	To	Thickness	<b>Well # 7434</b>					N486497.7 E632963					Fill - gravelly clay		0	8	8	Sandy lean clay		8	14	6	Caliche - hard off white		14	17	3	Sandy lean clay		17	20	3	Fat Clay - w/gravels		20	48	28	Caliche - hard off white		48	52	4	Fat Clay - w/gravels partially cem		52	61	9	<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>Depth Drilled</th> <th>61'</th> <th>Feet</th> <th>Depth Cased</th> <th>60'</th> <th>Feet</th> </tr> </thead> <tbody> <tr> <td colspan="6" style="text-align: center;">HOLE DIAMETER (BIT SIZE)</td> </tr> <tr> <td colspan="6" style="text-align: center;">From To</td> </tr> <tr> <td>24"</td> <td>Inches</td> <td>surface</td> <td>Feet</td> <td>61'</td> <td>Feet</td> </tr> <tr> <td></td> <td>Inches</td> <td></td> <td>Feet</td> <td></td> <td>Feet</td> </tr> <tr> <td colspan="6" style="text-align: center;">CASING SCHEDULE</td> </tr> <tr> <th>Size O.D. (Inches)</th> <th>Weight/Ft. (Pounds)</th> <th>Wall Thickness (Inches)</th> <th>From (Feet)</th> <th>To (Feet)</th> <th></th> </tr> <tr> <td>6.5</td> <td>3.6</td> <td>.280</td> <td>0</td> <td>30</td> <td></td> </tr> </tbody> </table>		Depth Drilled	61'	Feet	Depth Cased	60'	Feet	HOLE DIAMETER (BIT SIZE)						From To						24"	Inches	surface	Feet	61'	Feet		Inches		Feet		Feet	CASING SCHEDULE						Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)		6.5	3.6	.280	0	30	
Material	Water Strata	From	To	Thickness																																																																																																	
<b>Well # 7434</b>																																																																																																					
N486497.7 E632963																																																																																																					
Fill - gravelly clay		0	8	8																																																																																																	
Sandy lean clay		8	14	6																																																																																																	
Caliche - hard off white		14	17	3																																																																																																	
Sandy lean clay		17	20	3																																																																																																	
Fat Clay - w/gravels		20	48	28																																																																																																	
Caliche - hard off white		48	52	4																																																																																																	
Fat Clay - w/gravels partially cem		52	61	9																																																																																																	
Depth Drilled	61'	Feet	Depth Cased	60'	Feet																																																																																																
HOLE DIAMETER (BIT SIZE)																																																																																																					
From To																																																																																																					
24"	Inches	surface	Feet	61'	Feet																																																																																																
	Inches		Feet		Feet																																																																																																
CASING SCHEDULE																																																																																																					
Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)																																																																																																	
6.5	3.6	.280	0	30																																																																																																	
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>Well #7435</th> <th>Material</th> <th>From</th> <th>To</th> <th>Thickness</th> </tr> </thead> <tbody> <tr> <td colspan="5">N486500.6 E633863</td> </tr> <tr> <td>Fill - gravelly clay</td> <td></td> <td>0</td> <td>9</td> <td>9</td> </tr> <tr> <td>Sandy lean clay</td> <td></td> <td>9</td> <td>14</td> <td>5</td> </tr> <tr> <td>Caliche - hard off white</td> <td></td> <td>14</td> <td>16</td> <td>2</td> </tr> <tr> <td>Sandy lean clay</td> <td></td> <td>16</td> <td>20</td> <td>4</td> </tr> <tr> <td>Fat Clay - w/gravels</td> <td></td> <td>20</td> <td>48</td> <td>28</td> </tr> <tr> <td>Caliche - hard off white</td> <td></td> <td>48</td> <td>52</td> <td>4</td> </tr> <tr> <td>Fat Clay - w/gravels partially cem</td> <td></td> <td>52</td> <td>61</td> <td>9</td> </tr> </tbody> </table>		Well #7435	Material	From	To	Thickness	N486500.6 E633863					Fill - gravelly clay		0	9	9	Sandy lean clay		9	14	5	Caliche - hard off white		14	16	2	Sandy lean clay		16	20	4	Fat Clay - w/gravels		20	48	28	Caliche - hard off white		48	52	4	Fat Clay - w/gravels partially cem		52	61	9	Perforations: Type of perforation machine slot Size of perforation .032" From 30 feet to 60 feet From feet to feet From feet to feet From feet to feet From feet to feet Annular Seal: Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> Neat Cement to Pumped Poured Cement Grout to Pumped Poured Concrete Grout to Pumped Poured ≥30% Bentonite Grout to Pumped Poured Gravel Pack: X Yes No to Pumped X Poured Type: pea gravel Bentonite Chips: Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> to Pumped Poured Type:																																																						
Well #7435	Material	From	To	Thickness																																																																																																	
N486500.6 E633863																																																																																																					
Fill - gravelly clay		0	9	9																																																																																																	
Sandy lean clay		9	14	5																																																																																																	
Caliche - hard off white		14	16	2																																																																																																	
Sandy lean clay		16	20	4																																																																																																	
Fat Clay - w/gravels		20	48	28																																																																																																	
Caliche - hard off white		48	52	4																																																																																																	
Fat Clay - w/gravels partially cem		52	61	9																																																																																																	
Date started: 29-Jun 20 07 Date completed: 6/29/2007 20 07		10. DRILLER'S CERTIFICATION																																																																																																			
7. Water Level		This well was drilled under my supervision and the report is true to the best of my knowledge.																																																																																																			
Static water level: 33 feet below land surface		Name Griffin Dewatering Corp																																																																																																			
Artesian Flow: G.P.M. P.S.I.		Contractor																																																																																																			
Water Temperature: °F		Address 536 E. Maitland Street																																																																																																			
Quality:		Contractor																																																																																																			
8. WELL TEST DATA		Ontario, Ca 91761																																																																																																			
TEST METHOD: Bailer x Pump Air Lift		Nevada contractor's license number																																																																																																			
G.P.M. Draw Down (Feet Below Static) Time (Hours)		issued by the State Contractor's Board C-23 0031246																																																																																																			
		Nevada driller's license number issued by the																																																																																																			
		Division of Water Resources, the on-site driller M-2264																																																																																																			
		Signed <u>Griffin Dewater</u>																																																																																																			
		By driller performing actual drilling on site or contractor																																																																																																			
		Date July 9, 2007																																																																																																			

LAS VEGAS OFFICE