


STATE OF NEVADA  
DIVISION OF WATER RESOURCES  
**WELL DRILLER'S REPORT**

OFFICE USE ONLY  
Log No. 103506  
Permit No. \_\_\_\_\_  
Basin 212



PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340.

NOTICE OF INTENT NO. 31425

1. OWNER Clark County Aviation ADDRESS AT WELL LOCATION McCarren Airport Terminal 3  
MAILING ADDRESS P.O. Box 11005 5757 Wayne Newton Boulevard, Las Vegas, NV  
Las Vegas, Nv Subdivision Name: \_\_\_\_\_ County: Clark

2. LOCATION NW ¼ NW ¼ Sec 35 T 21S N/S R 61 E Latitude \_\_\_\_\_ UTM E \_\_\_\_\_ NAD 27  
PERMIT/WAIVER No. DW-1244A 162-35-101-018 Longitude \_\_\_\_\_ N \_\_\_\_\_ x NAD 83/WGS 84  
Issued by Water Resources Parcel No. 162-35-101-018

3. WORKED PERFORMED PROPOSED USE DEWATER 5. WELL TYPE  
New Well Replace Recondition Domestic Irrigation Test Cable Rotary RVC  
Deepen x Other Dewatering Well Municipal/Industrial Monitor Stock Air x Other Auger Bucket

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
<b>Well # 7419</b>				
N486854.9 E632911				
Clayey Gravel		0	3	
Caliche - white/hard		3	6	
Fat Clay-with sand, gravel		6	18	
Silty Clayey Sand - red, brown		18	21	
Clayey Gravel, cemented lenses		21	34	
Sandy Fat Clay, brown to tan		34	47	
Caliche - moderate cemented		47	49	
Caliche - hard		49	51	
<b>Well #7420</b>				
N4868567 E633011				
Clayey Gravel		0	3	
Caliche - white/hard		3	6	
Fat Clay-with sand, gravel		6	18	
Caliche - white/hard		18	21	
Clayey Gravel, cemented lenses		21	34	
Sandy Fat Clay, brown to tan		34	47	
Caliche - moderate cemented		47	49	
Caliche - hard		49	51	

9. WELL CONSTRUCTION

Depth Drilled 51' Feet Depth Cased 50' Feet

HOLE DIAMETER (BIT SIZE)

From \_\_\_\_\_ To \_\_\_\_\_  
24" Inches surface Feet 50' BGL Feet  
Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet  
Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6.5	3.6	.280	0	20

Perforations:

Type of perforation machine slot  
Size of perforation .032"

From 20 feet to 50 feet  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet

Annular Seal: Yes X No

Neat Cement \_\_\_\_\_ to \_\_\_\_\_ Pumped Poured  
Cement Grout \_\_\_\_\_ to \_\_\_\_\_ Pumped Poured  
Concrete Grout \_\_\_\_\_ to \_\_\_\_\_ Pumped Poured  
≥30% Bentonite Grout \_\_\_\_\_ to \_\_\_\_\_ Pumped Poured

Gravel Pack: X Yes No \_\_\_\_\_ to \_\_\_\_\_ Pumped X Poured  
Type: \_\_\_\_\_ pea gravel

Bentonite Chips: Yes X No \_\_\_\_\_ to \_\_\_\_\_ Pumped Poured  
Type: \_\_\_\_\_

Date started: 5-Jul , 20 07  
Date completed: 5-Jul , 20 07

7. Water Level  
Static water level: 26' feet below land surface  
Artesian Flow: \_\_\_\_\_ G.P.M. \_\_\_\_\_ P.S.I.  
Water Temperature: \_\_\_\_\_ °F  
Quality: \_\_\_\_\_

8. WELL TEST DATA

TEST METHOD:	Bailer	Pump	Air Lift
	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

**DCNR/DWR  
RECEIVED**

10. DRILLER'S CERTIFICATION

This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Griffin Dewatering Corp  
Contractor

Address 536 E. Maitland Street  
Contractor

Ontario, Ca 91761

Nevada contractor's license number \_\_\_\_\_  
issued by the State Contractor's Board C-23 0031246

Nevada driller's license number issued by the \_\_\_\_\_  
Division of Water Resources, the on-site driller M-2264

Signed [Signature]  
By driller performing actual drilling on site or contractor

Date 7/3/07

AUG 03 2007

**LAS VEGAS OFFICE**