STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 103582
Permit No.
Basin 049

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 60153

1. OWNER ERIC GOICOECHEA
MAILING ADDRESS 620 MAPLE STREET
ELKO, NV 89801

ADDRESS AT WELL LOCATION 1416 ROCKLAND DRIVE
N. OF MOUNTAIN CITY HWY.
Subdivision Name: PARCEL OF LAND County: ELKO

2. LOCATION NW ¼ NE ¼ Sec 7 T 34N N/S R 55 E
PERMIT/WAIVER No. 006-09B-073
Issued by Water Resources Parcel No.

Latitude 40.351073
Longitude 115.822059
UTM E 11T 0599293 [X] NAD 27
N 4522681 [ ] NAD 83/WGS 84

3. WORKED PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Other

4. PROPOSED USE
[X] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[X] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
TOPSOIL		0	1	1
GRAVEL & CLAY MIX		1	6	5
SILTSTONE		6	50	44
CEMENTED GRAVEL & Boulders		50	120	50
SILTSTONE & GRAVEL	500	120	560	440
	520			

Date started: 28-Jun , 20 07
Date completed: 29-Jun , 20 07

9. WELL CONSTRUCTION
Depth Drilled 560 Feet Depth Cased 560 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
10 5/8	Inches	0	Feet	560	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8	13.	.188	+1	560

Perforations:
Type of perforation MACHINED MILL SLOT
Size of perforation 3/16" X 3", 6 ROW
From 540 feet to 560 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: [X] Yes [ ] No
[X] Neat Cement 5 to 50 [ ] Pumped [X] Poured
[ ] Cement Grout to [ ] Pumped [ ] Poured
[ ] Concrete Grout to [ ] Pumped [ ] Poured
[ ] ≥30% Bentonite Grout to [ ] Pumped [ ] Poured

Gravel Pack: [X] Yes [ ] No 50 to 560 [ ] Pumped [X] Poured
Type: 3/8" PEA GRAVEL
Bentonite Chips: [ ] Yes [X] No to [ ] Pumped [ ] Poured
Type:

7. Water Level
Static water level: 399 feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature COLD °F
Quality:

8. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
25		3

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name HACKWORTH DRILLING, INC.
Contractor
Address P. O. BOX 850
Contractor
ELKO, NV 89803
Nevada contractor's license number issued by the *State Contractor's Board* 120582
Nevada driller's license number issued by the Division of Water Resources, the *on-site driller* 1689
Signed
By driller performing actual drilling on site or contractor
Date 7/3/2007

(Rev 05-06)

USE ADDITIONAL SHEETS IF NECESSARY