

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT



OFFICE USE ONLY
Log No. 103748
Permit No.
Basin 051

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in
accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 59814

1 OWNER Newmont Mining Corporation Incorporation
MAILING ADDRESS PO Box 669
Carlin, NV 89822

ADDRESS AT WELL LOCATION Gold Quarry
Subdivision Name: County: Eureka

2 LOCATION NW 1/4 NE 1/4 Sec 2 T 33N N/S R 51 E
PERMIT/WAIVER No. 618437 56838
Issued by Water Resources Parcel No.

Latitude UTM E 567135 [x] NAD 27
Longitude N 4514755 [] NAD 83/WGS 84

3 TYPE OF WELL
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock

Is this well being plugged because a replacement well was drilled? No
If yes, what is replacement well NOI?

Is there an existing well log? Yes
If yes, what is NDWR well log #?

4 EXISTING WELL CONSTRUCTION
Depth Drilled 402 Feet Depth Cased 400 Feet

7 WELL PLUGGING PROCEDURE
Was well cleaned out to total depth? [x] yes [] no
If well was not cleaned out to total depth, please explain why:

EXISTING CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
8	24.7	.250	0	400

Was the well contaminated? [] yes [x] no
Was the casing pulled? [] yes [x] no
Was the casing over drilled? [] yes [x] no
If casing was left in place, please show where additional perforations were made:
Additional Perforations:

Existing Perforations:

Type of perforation	Size of perforation	From	feet to	feet
Saw Cut	1/8" x 2 1/2" x 12/ft	150	feet to	400

Type of perforator used:

From	feet to	feet	Number of perfs per linear foot
From	feet to	feet	Number of perfs per linear foot
From	feet to	feet	Number of perfs per linear foot
From	feet to	feet	Number of perfs per linear foot
From	feet to	feet	Number of perfs per linear foot
From	feet to	feet	Number of perfs per linear foot
From	feet to	feet	Number of perfs per linear foot

5 WATER LEVEL
Static water level 302 feet below land surface
Artesian flow No G.P.M. N/A P.S.I.
Water temperature ° F Quality

8 WELL PLUGGING MATERIALS
Material Used

From 400 feet to 0 feet	abandonite	[x] Pumped	[] Poured
From 53 feet to 50 feet	3/8" hole plug	[] Pumped	[x] Poured
From 53 feet to 0 feet	neat cement	[x] Pumped	[] Poured
From feet to feet		[] Pumped	[] Poured
From feet to feet		[] Pumped	[] Poured
From feet to feet		[] Pumped	[] Poured

6 Additional Notes or Comments
Pumped 66 bags of abandonite slurry from bottom up until well was full. After abandonite subsided, poured bentonite to 53 ft pumped 7 bags neat cement from 53 to surface.
N 40.282942
W 116.204368 NAD22

Neat Cement Fluid Weight 15.8 lbs/gal
Bentonite Grout 12.5 % bentonite
Date Started 8/1/2007
Date Completed 8/2/2007

DRILLER'S CERTIFICATION
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.
Name Eklund Drilling Company, Inc.
Address PO Box 2748
Elko, NV 89803
Nevada contractor's license number issued by the State Contractor's Board 0030823
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1776
Signed Arthur Steelman
Date 8/24/2007

9 DRILLER'S CERTIFICATION
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.
Name Eklund Drilling Company, Inc.
Address PO Box 2748
Elko, NV 89803
Nevada contractor's license number issued by the State Contractor's Board 0030823
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1776
Signed Arthur Steelman
Date 8/24/2007