STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 104279
Permit No.
Basin 137B

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 59825

1. OWNER Gold Corp
MAILING ADDRESS PO Box 160
NW Valmy, NV 89438

ADDRESS AT WELL LOCATION Marigold Mine, Target
Subdivision Name: County: Humboldt

2. LOCATION ~~SE~~ ¼ SW ¼ Sec 5 ~~NE~~ T 33N N/S R 43 E
PERMIT/WAIVER No. M/O 1357A
Issued by Water Resources Parcel No.

Latitude
Longitude
UTM E 485973.00082 [X] NAD 27
N 4512152.00071 [ ] NAD 83/WGS 84

3. WORKED PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [X] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [ ] Rotary [ ] RVC
[X] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Alluvium		0	40	40
Bedrock		40	800	760

N 40.762116
W 117.166186 NAD27

Date started: 6-Sep , 20 07
Date completed: 13-Sep , 20 07

7. Water Level
Static water level: 508 feet below land surface
Artesian Flow: No G.P.M. N/A P.S.I.
Water Temperature: 73 °F
Quality: Good

8. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
100 PSI	20	N/A	

9. WELL CONSTRUCTION
Depth Drilled 800 Feet Depth Cased 800 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
11 1/2	Inches	0	Feet	20	Feet
8 3/4	Inches	20	Feet	800	Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4.5	Sch 80	.250 PVC	0	800

Perforations:
Type of perforation Slot
Size of perforation 0.02
From 580 feet to 780 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: [X] Yes [ ] No
[X] Neat Cement 0 to 52 [X] Pumped [ ] Poured
[ ] Cement Grout to [ ] Pumped [ ] Poured
[ ] Concrete Grout to [ ] Pumped [ ] Poured
[ ] ≥30% Bentonite Grout to [ ] Pumped [ ] Poured

Gravel Pack: [X] Yes [ ] No 800 to 578 [ ] Pumped [X] Poured
Type: 1/4" SRI Gravel
Bentonite Chips: [X] Yes [ ] No 518 to 52 [ ] Pumped [X] Poured
Type: 3/8 med hole plug

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Eklund Drilling Company, Inc. (Contractor)
Address PO Box 2748 (Contractor)
Elko, NV 89803
Nevada contractor's license number issued by the *State Contractor's Board* 0030823
Nevada driller's license number issued by the Division of Water Resources, the *on-site driller* 1777
Signed Dennis White by [illegible] (By driller performing actual drilling on site or contractor)
Date 9/13/2007

STATE ENGINEERS OFFICE
2007 SEP 24 PM 1:26
RECEIVED

(Rev. 05-06)

USE ADDITIONAL SHEETS IF NECESSARY