STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 104342
Permit No.
Basin 071

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 60229

1. OWNER Pedro Loyola
MAILING ADDRESS 6650 Germain Winnemucca, NV 89445
ADDRESS AT WELL LOCATION 6650 Germain Winnemucca, NV 89445
Subdivision Name: County: Humboldt

2. LOCATION SE ¼ SE ¼ Sec 12 T 35N N/S R 37 E
PERMIT/WAIVER No. 013-141-08 *Issued by Water Resources* Parcel No.
Latitude 40.918845 Longitude 117.755244
UTM E 436403 N 4529811 [x] NAD 27 [ ] NAD 83/WGS 84

3. WORKED PERFORMED
[x] New Well [ ] Replace [ ] Recondition [ ] Deepen [ ] Other

4. PROPOSED USE
[x] Domestic [ ] Irrigation [ ] Test [ ] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [x] Rotary [ ] RVC [ ] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Sand, Cobbles		0	25	25
sand, gravel, cobbles		25	45	20
gravel, cobbles		45	125	80
sand, cobbles	X	125	190	65

Date started: 1-Sep, 20 07
Date completed: 4-Sep, 20 07

RECEIVED 2007 OCT -5 AM 11:22 STATE ENGINEERS OFFICE

9. WELL CONSTRUCTION
Depth Drilled 190 Feet Depth Cased 190 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
10.625	Inches	0	Feet	190	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6.625		.188	+2	190

Perforations:
Type of perforation punched
Size of perforation 3/16 x 1
From 165 feet to 185 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: [x] Yes [ ] No
[ ] Neat Cement to [ ] Pumped [ ] Poured
[ ] Cement Grout to [ ] Pumped [ ] Poured
[x] Concrete Grout 4 to 54 [ ] Pumped [x] Poured
[ ] ≥30% Bentonite Grout to [ ] Pumped [ ] Poured
Gravel Pack: [x] Yes [ ] No 54 to 190 [ ] Pumped [x] Poured
Type: 3/8 minus
Bentonite Chips: [ ] Yes [ ] No to [ ] Pumped [ ] Poured
Type:

7. Water Level
Static water level: 93 feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: cool °F
Quality: good

8. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [x] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
25		1

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name American Drilling & Pump Service (Contractor)
Address 3040 Callahan St (Contractor)
Winnemucca, NV 89445
Nevada contractor's license number issued by the *State Contractor's Board* 0020578
Nevada driller's license number issued by the Division of Water Resources, the *on-site driller* 2208
Signed [signature] (By driller performing actual drilling on site or contractor)
Date 10-3-07

(Rev. 05-06)
USE ADDITIONAL SHEETS IF NECESSARY