


SP-32

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY
Log No. 104675
Permit No.
Basin 052

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in
accordance with NRS 534.170 and NAC 534.340



NOTICE OF INTENT NO. 61480
ADDRESS AT WELL LOCATION Hamilton & main street
W.P.R.R. Rail Yard
County: Elko

1 OWNER Union Pacific Railroad
MAILING ADDRESS 221 Hodgeman
SW 33 Laramie, WY 82072

Subdivision Name:
Latitude N 40 42.740
Longitude W 116 06.201

2 LOCATION NE 1/4 SW 33 Laramie, WY 82072
PERMIT/WAIVER No. R-557
Issued by Water Resources Parcel No.

UTM E NAD 27
NAD 83/WGS 84

3 TYPE OF WELL
 Domestic
 Municipal/Industrial
 Irrigation
 Monitor
 Test
 Stock

Is this well being plugged because a replacement well was drilled? NO
If yes, what is replacement well NOI?

Is there an existing well log? NO
If yes, what is NDWR well log #?

4 EXISTING WELL CONSTRUCTION
Depth Drilled 20 Feet
Depth Cased 20 Feet

7 WELL PLUGGING PROCEDURE
Was well cleaned out to total depth? yes no
If well was not cleaned out to total depth, please explain why:

EXISTING CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2"		Sch 40 PVC	0	10

Was the well contaminated? yes no
Was the casing pulled? yes no
Was the casing over drilled? yes no
If casing was left in place, please show where additional perforations were made:

Existing Perforations:
Type of perforation Factory machine
Size of perforation 020
From 10 feet to 20 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Additional Perforations:
Type of perforator used:
From feet to feet Number of perfs per linear foot
From feet to feet Number of perfs per linear foot
From feet to feet Number of perfs per linear foot
From feet to feet Number of perfs per linear foot
From feet to feet Number of perfs per linear foot
From feet to feet Number of perfs per linear foot

5 WATER LEVEL
Static water level 13 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature 53 °F Quality

8 WELL PLUGGING MATERIALS
Material Used
From -2 feet to 20 feet Bentonite Pumped Poured
From feet to feet Pumped Poured

6 Additional Notes or Comments
Nocked out bottom with 140lb
Hammer, treamed Bent. grout
From bottom up, removed monument
capped with concrete.

Neat Cement Fluid Weight lbs/gal
Bentonite Grout 30% solids % bentonite
Date Started 9-28-07
Date Completed 10-1-07

N 40.512432
W 116.110782 NAD22
STATE ENGINEERS OFFICE
2007 OCT 22 PM 2:52
RECEIVED

9 DRILLER'S CERTIFICATION
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.
Name Environmental West Exploration Contractor
Address PO Box 11095 Spokane WA 99211 Contractor
Nevada contractor's license number issued by the State Contractor's Board 0028363
Nevada driller's license number issued by the Division of Water Resources, the on-site driller waiver # R-557
Signed [Signature] By driller performing actual drilling on site or contractor
Date 10-8-07