

Sp-17

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY
Log No. 104580
Permit No.
Basin 052

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in
accordance with NRS 534.170 and NAC 534.340

1 OWNER Union Pacific Railroad ADDRESS AT WELL LOCATION Hamilton # main street
MAILING ADDRESS 221 Hodge man UPRR Rail Yard
SW 1/4 Sec 27 T 33 S 2 R 557 Subdivision Name: Elko County
2 LOCATION 1/4 Sec 27 T 33 S 2 R 557 Latitude N: 40 42.618 UTM E NAD 27
PERMIT/WAIVER No. R-557 Longitude W: 116 06.563 N NAD 83/WGS 84

3 TYPE OF WELL: Domestic, Irrigation, Test, Municipal/Industrial, Monitor, Stock
Is this well being plugged because a replacement well was drilled? NO
Is there an existing well log? NO

4 EXISTING WELL CONSTRUCTION
Depth Drilled 20 Feet Depth Cased 20 Feet
EXISTING CASING SCHEDULE

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|--------------------|---------------------|-------------------------|-------------|-----------|
| 2" | | sch. 40 PVC | 0+3 | 20 |

7 WELL PLUGGING PROCEDURE
Was well cleaned out to total depth? yes no
If well was not cleaned out to total depth, please explain why:
Was the well contaminated? yes no
Was the casing pulled? yes no
Was the casing over drilled? yes no

Existing Perforations:

| Type of perforation | Size of perforation | From | feet to | feet |
|---------------------|---------------------|------|---------|------|
| Factory machine | 1070 | 10 | feet to | 20 |

Additional Perforations:

| Type of perforator used: | From | feet to | feet | Number of perfs per linear foot |
|--------------------------|------|---------|------|---------------------------------|
| | | | | |

5 WATER LEVEL
Static water level 13 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature 53 °F Quality

8 WELL PLUGGING MATERIALS

| From | feet to | feet | Material Used | <input checked="" type="checkbox"/> Pumped | <input type="checkbox"/> Poured |
|------|---------|------|---------------|--|---------------------------------|
| -2 | feet to | 20 | Bentonite | <input checked="" type="checkbox"/> | <input type="checkbox"/> |

6 Additional Notes or Comments
Knocked out Bottom with 140 lb hammer, tremmed Bent grout from Bottom up, removed monument capped with concrete
N 40, 710395
W 116, 109465 NAD 27

Neat Cement Fluid Weight lbs/gal
Bentonite Grout 30% Solids % bentonite
Date Started 9-28-07
Date Completed 10-1-07

STATE ENGINEERS OFFICE
2007 OCT 22 PM 2:52

9 DRILLER'S CERTIFICATION
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.
Name Environmental West Exploration Contractor
Address PO Box 11095 Spokane WA 99211 Contractor
Nevada contractor's license number issued by the State Contractor's Board 0028363
Nevada driller's license number issued by the Division of Water Resources, the on-site driller Waiver # R-557
Signed [Signature] By driller performing actual drilling on site or contractor
Date 10-8-07