

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY
Log No. 104592
Permit No. _____
Basin 953

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in
accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 61480

1 OWNER Union Pacific Railroad ADDRESS AT WELL LOCATION Hamilton & main street
MAILING ADDRESS 221 Hodge man UPRR Rail Yard
SE 1/4 SE 1/4 Laramie, WY 82072 Subdivision Name: _____ County: Elko

2 LOCATION 1/4 Sec 27 T 33 N SR 52 E Latitude N 40 42.695 UTM E _____ NAD 27
PERMIT/WAIVER NO. R-557 Longitude W 116 06.651 N _____ NAD 83/WGS 84

Issued by Water Resources Parcel No. _____

3 TYPE OF WELL
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock

Is this well being plugged because a replacement well was drilled? NO
If yes, what is replacement well NOI? _____

Is there an existing well log? NO
If yes, what is NDWR well log #? _____

4 EXISTING WELL CONSTRUCTION
Depth Drilled 15 Feet Depth Cased 15 Feet

EXISTING CASING SCHEDULE

Size O.D. (Inches)	Weight/Fl. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
<u>12"</u>		<u>sk 40 PVC</u>	<u>-3</u>	<u>8</u>

7 WELL PLUGGING PROCEDURE
Was well cleaned out to total depth? yes no
If well was not cleaned out to total depth, please explain why: _____

Existing Perforations:

Type of perforation	Size of perforation	From	feet to	feet
<u>Factory machine</u>	<u>0.70</u>	<u>8</u>	<u>15</u>	

Was the well contaminated? yes no
Was the casing pulled? yes no
Was the casing over drilled? yes no

If casing was left in place, please show where additional perforations were made:
Additional Perforations:
Type of perforator used: _____

From	feet to	feet	Number of perfs per linear foot

5 WATER LEVEL
Static water level 13 feet below land surface
Artesian flow _____ G.P.M. _____ P.S.I.
Water temperature 53 °F Quality _____

8 WELL PLUGGING MATERIALS

From	feet to	feet	Material Used	<input checked="" type="checkbox"/> Pumped	<input type="checkbox"/> Poured
<u>-3</u>	<u>15</u>		<u>Bentonite</u>		

6 Additional Notes or Comments
Knocked out bottom with 140lb. hammer. Tremmed Bent grout from bottom up. removed lids. Filled annulus with gravel.
N 40.711679
W 116.109932 NAD83

Neat Cement Fluid Weight _____ lbs/gal
Bentonite Grout 30% Solids % bentonite
Date Started 9-28-07
Date Completed 10-1-07

STATE ENGINEERS OFFICE
2007 OCT 22 PM 2:52

9 DRILLER'S CERTIFICATION
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.
Name Environmental West Exploration Contractor
Address PO Box 11095 Spokane WA 99211 Contractor
Nevada contractor's license number 0028363 issued by the State Contractor's Board
Nevada driller's license number issued by the Division of Water Resources, the on-site driller Waiver #R-557
Signed [Signature] By driller performing actual drilling on site or contractor
Date 10-8-07