

TS-01P

STATE OF NEVADA  
DIVISION OF WATER RESOURCES  
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY  
Log No. 104598  
Permit No.  
Basin 053

PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK

Please complete this form in its entirety in  
accordance with NRS 534.170 and NAC 534.340

1 OWNER Union Pacific Railroad ADDRESS AT WELL LOCATION Hamilton & main street  
MAILING ADDRESS 221 Hodgeman W.P.R.R. Rail Yard  
3W SE Laramie, WY 82072 Subdivision Name: County: Elko  
2 LOCATION N 1/4 Sec 27 T 33 R 52 E latitude N 40 42.703 UTM E  NAD 27  
PERMIT/WAIVER No. R-557 Longitude W 116 06.634 N  NAD 83/WGS 84

3 TYPE OF WELL  Domestic  Irrigation  Test  Municipal/Industrial  Monitor  Stock  
Is this well being plugged because a replacement well was drilled? NO  
If yes, what is replacement well NOI?  
Is there an existing well log? NO  
If yes, what is NDWR well log #?

4 EXISTING WELL CONSTRUCTION  
Depth Drilled 15 Feet Depth Cased 15 Feet  
EXISTING CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6"		Sch 40 PVC	-3	8

7 WELL PLUGGING PROCEDURE  
Was well cleaned out to total depth?  yes  no  
If well was not cleaned out to total depth, please explain why:  
Was the well contaminated?  yes  no  
Was the casing pulled?  yes  no  
Was the casing over drilled?  yes  no  
If casing was left in place, please show where additional perforations were made:  
Additional Perforations:  
Type of perforator used:  
From feet to feet Number of perms per linear foot

Existing Perforations:

Type of perforation	Size of perforation	From	feet to	feet
Factory machine	1.020	8	feet to	15 feet

Additional Perforations:

From	feet to	feet	Number of perms per linear foot

5 WATER LEVEL  
Static water level 13 feet below land surface  
 Artesian flow G.P.M. P.S.I.  
Water temperature 53 °F Quality

8 WELL PLUGGING MATERIALS

From	feet to	feet	Material Used	<input checked="" type="checkbox"/> Pumped	<input type="checkbox"/> Poured
-3	feet to	15 feet	Bentonite	<input checked="" type="checkbox"/>	<input type="checkbox"/>
				<input type="checkbox"/>	<input type="checkbox"/>
				<input type="checkbox"/>	<input type="checkbox"/>
				<input type="checkbox"/>	<input type="checkbox"/>
				<input type="checkbox"/>	<input type="checkbox"/>
				<input type="checkbox"/>	<input type="checkbox"/>
				<input type="checkbox"/>	<input type="checkbox"/>

6 Additional Notes or Comments  
Nocked out bottom with 140 lb hammer tremmed Bent grout from bottom up removed lids Filled vaults with gravel.

Neat Cement Fluid Weight lbs/gal  
Bentonite Grout 30% Solids % bentonite  
Date Started 9-25-07  
Date Completed 10-1-07

N 40.711812  
W 116.109648 NAD27  
STATE ENGINEERS OFFICE  
2007 OCT 22 PM 2:52  
RECEIVED

9 DRILLER'S CERTIFICATION  
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.  
Name Environmental West Exploration Contractor  
Address PO Box 11095 Spokane WA 99211 Contractor  
Nevada contractor's license number issued by the State Contractor's Board 0028363  
Nevada driller's license number issued by the Division of Water Resources, the on-site driller waiver # R-557  
Signed [Signature] By driller performing actual drilling on site or contractor  
Date 10-8-07