STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 104647
Permit No.
Basin Ø71

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 58478

1. OWNER RICH BROWN
MAILING ADDRESS 4790 BRAYTON
Winnemucca, Nv 89445

ADDRESS AT WELL LOCATION 4790 BRAYTON
Winnemucca, Nv 89445
Subdivision Name: Sonoma ranchos #1 County: Humboldt

2. LOCATION SE ¼ SE ¼ Sec 7 T 35N N/S R 38E
PERMIT/WAIVER No. n/a 010-484-53
Issued by Water Resources Parcel No.

Latitude 40 55.123N UTM E [ ] NAD 27
Longitude 117 44.463W N [x] NAD 83/WGS 84

3. WORKED PERFORMED
[x] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Other

4. PROPOSED USE
[x] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [x] Rotary [ ] RVC
[ ] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Cobbles & gravel		0	20	20
Sand, gravel & cobbles		20	80	60
consolidated sand & gravel		80	140	60
Sand & Gravel		140	170	30
sand & gravel mixed with clay		170	175	5
Sand & gravel		175	200	25
Softer sand & gravel	40	200	240	40
				240

~~N 40.918712~~
~~W 117.741058 NAD83~~

RECEIVED 2007 OCT 25 PM 2:44 STATE ENGINEERS OFFICE

Date started: Sept 10 20 06
Date completed: sept 15 20 06

7. *Water Level*
Static water level: 201 feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: °F
Quality:

8. WELL TEST DATA

TEST METHOD:	Bailer G.P.M.	Pump Draw Down (Feet Below Static)	Air Lift x Time (Hours)
Air	22	12	4

9. *WELL CONSTRUCTION*
Depth Drilled 240 Feet Depth Cased 240

HOLE DIAMETER (BIT SIZE)

		From		To	
10 5/8	Inches	0	Feet	240	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6.50	steel	.25	0	20
6.75	pvc	.35	20	240

Perforations:
Type of perforation PVC Screen
Size of perforation 1/32
From 200 feet to 240 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: Yes

[ ]	Neat Cement	to		[ ] Pumped	[ ] Poured
[ ]	Cement Grout	to		[ ] Pumped	[x] Poured
[x]	Concrete Grout	0 to 50		[ ] Pumped	[ ] Poured
[ ]	≥30% Bentonite Grout	to		[ ] Pumped	[ ] Poured

Gravel Pack: [x] Yes [ ] No 50 to 240 [ ] Pumped [x] Poured
Type: 3/8 minus
Type: ~~3/8 baroid~~

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name High Desert Drilling LLC
Contractor
Address 4225 E Mary Way
Contractor
Winnemucca Nevada 89445
Nevada contractor's license number issued by the *State Contractor's Board* 62237
Nevada driller's license number issued by the Division of Water Resources, the *on-site driller* 2140
Signed [signature]
By driller performing actual drilling on site or contractor
Date 9-20-06

(Rev. 05-06) USE ADDITIONAL SHEETS IF NECESSARY

STATE ENGINEERS OFFICE
2006 DEC 15 PM 2:42
RECEIVED

N 40.918828
W 117.740082 NAD27