


STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT



OFFICE USE ONLY
Log No. 104705
Permit No. _____
Basin 138

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in
accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 61251

1. OWNER Barrick/Cortez Gold Mines ADDRESS AT WELL LOCATION Cortez Hills
MAILING ADDRESS HC 66 Box 1250 Hole #CHPZ-60
Crescent Valley, NV 89821 Subdivision Name: _____ County: Lander

2. LOCATION NE 1/4 SW 1/4 Sec 6 T 26N N/S R 48 E Latitude 40.151970 UTM E 533273.593 NAD 27
PERMIT/WAIVER No. M/O-1472 Longitude 116.609335 N 4444487.479 NAD 83/WGS 84
Issued by Water Resources Parcel No. _____

3. WORKED PERFORMED
 New Well Replace Recondition
 Deepen Other

4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock

5. WELL TYPE
 Cable Rotary RVC
 Air Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Badly Broken Gravel, Aluvium		0	170	170
Gravel, sands, clays		170	870	700
bedrock @870'				
Volcanic - Gray- green with oxidated		870	1380	510
Black rock, some volcanic mix		1380	1420	40
1st noticed water @ 520'				
2 gpm water	600'			
9 gpm water	700'			
17 gpm water	720'			
59 gpm water	900'			
75 gpm water	1000'			
136 gpm water	1420'			

9. WELL CONSTRUCTION

Depth Drilled	Feet	Depth Cased	Feet
1420		1420	

HOLE DIAMETER (BIT SIZE)

From	To
12 1/4 Inches	0 Feet 40 Feet
6 3/4 Inches	40 Feet 1000 Feet
6 1/2 Inches	1000 Feet 1420 Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
8		.188	0	40
2		Sch 80 pvc	0	1420

Perforations:

Type of perforation Slotted
Size of perforation 0.02

From Blank pvc 0 feet to 1400 feet
From Slotted pvc 1400 feet to 1420 feet
From _____ feet to _____ feet
From _____ feet to _____ feet

Annular Seal: Yes No

Neat Cement _____ to 51 Pumped Poured
 Cement Grout _____ to _____ Pumped Poured
 Concrete Grout _____ to _____ Pumped Poured
 ≥30% Bentonite Grout 460 to 1398 Pumped Poured

Gravel Pack: Yes No 1398 to 1420 Pumped Poured
Type: #8 Gravel

Bentonite Chips: Yes No 51 to 460 Pumped Poured
Type: 3/8" bentonite hole plug

Date started: 31-Oct , 20 07
Date completed: 5-Nov , 20 07

7. Water Level
Static water level: 490 feet below land surface
Artesian Flow: No G.P.M. N/A P.S.I.
Water Temperature: Cool °F
Quality: Good

8. WELL TEST DATA

TEST METHOD:	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input type="checkbox"/> Air Lift			
N/A			
136 gpm at 1420' while drilling			

10. DRILLER'S CERTIFICATION

This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Eklund Drilling Company, Inc. Contractor
Address PO Box 2748 Contractor
Elko, NV 89803

Nevada contractor's license number issued by the State Contractor's Board 0030823
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M-2290

Signed August Wildeman by driller performing actual drilling on site or contractor
Date 11/6/2007

(Rev. 05-08)

USE ADDITIONAL SHEETS IF NECESSARY