STATE OF NEVADA
DIVISION OF WATER RESOURCES
# WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 104709
Permit No.
Basin Ø42

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

*Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340*

NOTICE OF INTENT NO. 60165

1. OWNER ~~CHUCK SALLEE~~ - Janice Pendelton?
MAILING ADDRESS P. O. BOX 871
WELLS, NV 89835

ADDRESS AT WELL LOCATION ~~[illegible]~~ ANGEL LAKE ROAD
WELLS, NV
Subdivision Name: Elko County:

2. LOCATION SW ¼ SW ¼ Sec 8 T 37N N/S R 62 E
PERMIT/WAIVER No. 008-340~~024~~ 025
Issued by Water Resources Parcel No.

Latitude 41.097400 UTM E 11T 0667842 [X] NAD 27
Longitude 115.001458 N 4551282 [ ] NAD 83/WGS 84

3. WORKED PERFORMED
[ ] New Well [X] Replace [ ] Recondition
[ ] Deepen [ ] Other

4. PROPOSED USE
[X] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[X] Air [ ] Other

6. LITHOLOGIC LOG

| Material | Water Strata | From | To | Thickness |
|---|---|---|---|---|
| TOPSOIL | | 0 | 2 | 2 |
| BROWN CLAY | | 2 | 8 | 6 |
| SILTSTONE | | 8 | 120 | 112 |
| BLACK VOLCANIC | 200 | 120 | 220 | 100 |
| VOLCANIC ASH | | 220 | 360 | 140 |
| BLUE CLAY | 460 | 360 | 480 | 120 |

Date started: 31-Jul , 20 07
Date completed: 3-Aug , 20 07

9. WELL CONSTRUCTION
Depth Drilled 480 Feet Depth Cased 480 Feet

HOLE DIAMETER (BIT SIZE)

| | | From | | To | |
|---|---|---|---|---|---|
| 10 5/8 | Inches | 0 | Feet | 480 | Feet |
| | Inches | | Feet | | Feet |
| | Inches | | Feet | | Feet |

CASING SCHEDULE

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|---|---|---|---|---|
| 6.625 | 13 | .188 | +1 | 480 |

Perforations:
Type of perforation MACHINED MILL SLOT
Size of perforation 3/16" X 3", 6 ROW
From 180 feet to 220 feet
From 440 feet to 480 feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: [X] Yes [ ] No
[X] Neat Cement 5 to 50 [ ] Pumped [X] Poured
[ ] Cement Grout to [ ] Pumped [ ] Poured
[ ] Concrete Grout to [ ] Pumped [ ] Poured
[ ] ≥30% Bentonite Grout to [ ] Pumped [ ] Poured

Gravel Pack: [X] Yes [ ] No 50 to 480 [ ] Pumped [X] Poured
Type: 3/8" PEA GRAVEL
Bentonite Chips: [ ] Yes [X] No to [ ] Pumped [ ] Poured
Type:

7. Water Level
Static water level: 160 feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: °F
Quality:

8. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

| G.P.M. | Draw Down (Feet Below Static) | Time (Hours) |
|---|---|---|
| 11.5 | | 10 |

STATE ENGINEERS OFFICE
2007 NOV -5 AM 11:36
RECEIVED

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name HACKWORTH DRILLING, INC.
Contractor
Address P. O. BOX 850
Contractor
ELKO, NV 89803
Nevada contractor's license number issued by the *State Contractor's Board* 020582
Nevada driller's license number issued by the Division of Water Resources, the *on-site driller* 1689
Signed [signature]
By driller performing actual drilling on site or contractor
Date 8/9/2007

(Rev 05-06)

USE ADDITIONAL SHEETS IF NECESSARY