


REVISED

STATE OF NEVADA  
DIVISION OF WATER RESOURCES  
WELL DRILLER'S REPORT

OFFICE USE ONLY  
Log No. 104720  
Permit No.  
Basin 056

PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK  
Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340



This replacement well was drilled in the wrong 1/4 M, but within 300' of permitted location AC 1-30-08

1. OWNER Lee Hutchens ADDRESS AT WELL LOCATION Well # 4 Austin  
MAILING ADDRESS 4280 Rancheria Rd.  
NE NW Fallon, NV 89406

2. LOCATION NW 1/4 NE 1/4 Sec 12 T 17N N/S R 41 E Latitude 39.35951 UTM E NAD 27  
PERMIT/WAIVER No. 21280 Longitude 117.31593 N NAD 83/WGS 84  
Issued by Water Resources Parcel No. Subdivision Name: County: Lander

3. WORKED PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Other....  
4. PROPOSED USE  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock  
5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other.....

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Gravel and clay		0	60	60
Sandy clay		60	115	55
Sand and gravel		115	125	10
Sandy clay		125	135	10
Sand and gravel		135	140	5
Clay		140	143	3
Sand and gravel		143	147	4
Sand and clay		147	150	3
Sand and gravel		150	160	10
Sandy clay		160	165	5
Sand and gravel		165	170	5
Sandy clay		170	175	5
Sand and gravel		175	180	5
Sandy clay		180	185	5
Sand and gravel		185	196	11
Sandy clay		196	215	19
Sand and gravel		215	240	25
Sandy clay		240	243	3
Sand and gravel		243	250	7
Sandy clay		250	275	25
Sand and gravel		275	278	3
Sandy clay		278	280	2
Sand and gravel		280	312	32
Sandy clay		312	330	18

8. WELL CONSTRUCTION  
Depth Drilled 330 Feet Depth Cased 320 Feet  
HOLE DIAMETER (BIT SIZE)  
From To  
38 Inches 0 Feet 50 Feet  
24 Inches 50 Feet 330 Feet  
CASING SCHEDULE  
Size O.D. (Inches) Weight/Ft. (Pounds) Wall Thickness (Inches) From (Feet) To (Feet)  
16 .250 +2 40  
30 .250 +1 50  
Perforations:  
Type of perforation Mill slot  
Size of perforation 0.09  
From 40 feet to 320 feet  
From feet to feet  
From feet to feet  
From feet to feet  
Surface Seal:  Yes  No Seal Type:  
Depth of Seal 50  Neat Cement  
Placement Method:  Pumped  Concrete Grout  
 Poured  
Gravel Packed:  Yes  No  
From 5 feet to 330 feet

Date started 4/2/2007 20  
Date completed 4/4/2007 20

7. WELL TEST DATA

TEST METHOD:	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input checked="" type="checkbox"/> Air Lift	1000	52	8.5

STATE ENGINEERS OFFICE  
20-2111-1-10N1002  
NOV-1-2007

9. WATER LEVEL  
Static water level 67 feet below land surface  
Artesian flow G.P.M. P.S.I.  
Water temperature cool °F Quality good

10. DRILLER'S CERTIFICATION  
This well was drilled under my supervision and the report is true to the best of my knowledge.  
Name Hydro Resources Nevada, Inc. dba Humboldt Drilling & Pump Contractor  
Address 4975 W. Winnemucca Blvd. Winnemucca, NV 89445 Contractor  
Nevada contractor's license number issued by the State Contractor's Board 56797  
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1713  
Signed Judi Leach, Office  
By driller performing actual drilling on site or contractor  
Date 4/20/2007

(Rev. 12-06)

USE ADDITIONAL SHEETS IF NECESSARY

REVISED 10/29/2007