STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 104723
Permit No.
Basin Ø71

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 58472

1. OWNER Mathew Hislop — ADDRESS AT WELL LOCATION 6380 Germain
MAILING ADDRESS 6380 Germain — Winnemucca Nv 89445
Winnemucca Nv 89445 — Subdivision Name: — County: HUMBOLDT

2. LOCATION NE ¼ NE ¼ Sec 12 T T35N N/S R R37E E — Latitude 40 55.627n — UTM E — NAD 27
PERMIT/WAIVER No. 0 — 013-476-13 — Longitude 117 45.374W wgs — N — [X] NAD 83/WGS 84
Issued by Water Resources — Parcel No. 013-475-13

3. WORKED PERFORMED: [X] New Well — Replace — Recondition — Deepen — Other

4. PROPOSED USE: [X] Domestic — Irrigation — Test — Municipal/Industrial — Monitor — Stock

5. WELL TYPE: Cable — [X] Rotary — RVC — Air — Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
topsoil		0	4	4
sand & Gravel		4	125	121
Coarse sand & gravel		125	180	55
		180		-180
N 40.927228				
W 117.755265				

Date started: 6-8-07, 20 07
Date completed: 6-9-07, 20 07

9. WELL CONSTRUCTION
Depth Drilled 180 Feet — Depth Cased 180

HOLE DIAMETER (BIT SIZE)

		From		To	
10 5/8	Inches	0	Feet	60	Feet
6.5	Inches	60	Feet	180	Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6.5	STEEL	.188	0	180

Perforations:
Type of perforation torched
Size of perforation 1/16
From 140 feet to 180 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: Yes
Neat Cement to Pumped Poured
Cement Grout 4 to 60 [ ] Pumped [X] Poured
Concrete Grout to Pumped Poured
≥30% Bentonite Grout to Pumped Poured
Gravel Pack: Yes [redacted] 60 to 180 Pumped Poured
Type:
Bentonite Chips: [redacted] Yes No to Pumped [X] Poured
Type: ~~3/8 baroid~~

7. Water Level
Static water level: 83 feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: COLD °F
Quality:

8. WELL TEST DATA
TEST METHOD: Bailer — Pump — Air Lift x

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
AIR	25	30	4

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name (Contractor) High Desert Drilling LLC
Address (Contractor) 4225 E Mary Way
Winnemucca Nevada 89445
Nevada contractor's license number issued by the State Contractor's Board 62237
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2140
Signed [signature]
By driller performing actual drilling on site or contractor
Date 6-27-07

USE ADDITIONAL SHEETS IF NECESSARY

STATE ENGINEERING OFFICE
2007 JUN 28 AM 11:14