STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 104761
Permit No.
Basin 066

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 61245

1. OWNER Newmont Mining Corp.
MAILING ADDRESS PO Box 388
Valmy, NV 89435

ADDRESS AT WELL LOCATION Twin Creeks Mine
Hole #TMO-30044
Subdivision Name: County: Humboldt

2. LOCATION SW ¼ NE ¼ Sec 30 T 39N N/S R 43 E
PERMIT/WAIVER No. M/O-1467
Issued by Water Resources Parcel No.

Latitude 41.235263 Longitude 117.167859
UTM E 485932.76467 N 4564675.297725 [x] NAD 27 [ ] NAD 83/WGS 84

3. WORKED PERFORMED
[x] New Well [ ] Replace [ ] Recondition [ ] Deepen [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [ ] Test [ ] Municipal/Industrial [x] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [ ] Rotary [ ] RVC [x] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Bedrock		0	800	800
Pumped 15 lb per gallon neat cement from bottom of hole to 200' of surface, 1200 gallons total.				

Plugged by # 111296

Date started: 19-Oct , 20 07
Date completed: 31-Oct , 20 07

7. Water Level
Static water level: 112 feet below land surface
Artesian Flow: No G.P.M. N/A P.S.I.
Water Temperature: 83 °F
Quality: Good

8. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [x] Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
@800' 300 PSI	200+	N/A	1

9. WELL CONSTRUCTION
Depth Drilled 800 Feet Depth Cased 190 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
9 1/4	Inches	0	Feet	20	Feet
6 3/4	Inches	20	Feet	800	Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2 3/8	Sch 80	.250	0	190

Perforations:
Type of perforation Slotted
Size of perforation 0.125
From 170 feet to 130 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: [x] Yes [ ] No
[x] Neat Cement 51 to 0 [x] Pumped [ ] Poured
[ ] Cement Grout to [ ] Pumped [ ] Poured
[ ] Concrete Grout to [ ] Pumped [ ] Poured
[ ] ≥30% Bentonite Grout to [ ] Pumped [ ] Poured
Gravel Pack: [x] Yes [ ] No 190 to 129 [ ] Pumped [x] Poured
Type: SRI 3/8 Gravel
Bentonite Chips: [x] Yes [ ] No 129 to 51 [ ] Pumped [x] Poured
Type: 3/8 Med Hole Plug M/I

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Eklund Drilling Company, Inc. (Contractor)
Address PO Box 2748 (Contractor)
Elko, NV 89803
Nevada contractor's license number issued by the *State Contractor's Board* 0030823
Nevada driller's license number issued by the Division of Water Resources, the *on-site driller* 1777
Signed Dennis L White by (By driller performing actual drilling on site or contractor)
Date 10/31/2007

STATE ENGINEER'S OFFICE
2007 NOV -9 AM 10:59
RECEIVED

(Rev. 05-06)
USE ADDITIONAL SHEETS IF NECESSARY

no. F.