

STATE OF NEVADA
 DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY

Log No. 105058
 Permit No. _____
 Basin 153

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK



Please fill in this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 59212

1. OWNER Diamond Valley Ranch
 MAILING ADDRESS P.o. Box 920 Lake Oswego, OR 970
 Lake Oswego, OR 97034

ADDRESS AT WELL LOCATION Diamond Valley #8
 Eureka, NV 89316

2. LOCATION SE 1/4 NE 1/4 Sec 22 T 21 R 53
 PERMIT NO 20066 Parcel No.

Latitude ~~39.67582~~ Longitude ~~115.98877~~ WGS 84
 Subdivision Name _____ County Eureka

3. TYPE OF WELL Irrigation
 Is this well being plugged because a replacement well was drilled? Yes
 If yes what is replacement well NOI? 105# 76595

Is there an existing well log? Yes
 If yes, what is NDWR well log #? 6978

4. EXISTING WELL CONSTRUCTION
 Depth Drilled 260 Feet Depth Cased 260 Feet

EXISTING CASING SCHEDULE

Size O.D. (inches)	Weight/Ft. (Pounds)	Wall Thickness	From (Feet)	To (Feet)
16	42.0	0.250	0	260

Existing Perforations:

Type perforation Mill Cut
 Size perforation 0.250
 From 226 feet to 238 feet
 From 252 feet to 260 feet
 From 100 feet to 204 feet

7. WELL PLUGGING PROCEDURE

Was well cleaned out to total depth? Yes
 If well was not cleaned out to total depth, please explain why:

Was well contaminated? No
 Was casing pulled? No
 Was casing overdrilled? No

If casing was left in place, please show where additional perforations were made:

Additional Perforations:

Type perforator used: Air Roller
 From 0 To 100 Number of perfs per linear foot 16
 From 205 To 222 Number of perfs per linear foot 16
 From 240 To 250 Number of perfs per linear foot 16

5. WATER LEVEL

Static Water Level 96 feet below land surface
 Artesian Flow G.P.M. P.S.I.
 Water temperature ° F Quality

8. WELL PLUGGING MATERIALS

Material
 From 0 Feet to 50 Feet Neat Cement Pumped
 From 50 Feet to 260 Feet Bentonite Pumped

6. Additional Notes or Comments

Pumped in 75 bags of 20% Bentonite grout from bottom to 50 ft.
 Installed 3 yds of neat cement from 50 ft. to surface.

N39.675624
W115.987621 NAD27

Neat Cement Fluid Weight 156 lbs/gal
 Bentonite Grout 20 % Bentonite
 Date Started 3/14/2007
 Date Completed 11/6/2007

9. DRILLER'S CERTIFICATION

This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Parsons Drilling, Inc.
 Contracto
 Address 403 McLean Road
 Fallon, NV 89407

Contracto
 Nevada contractor's license number 29064
 issued by the State Contractor's Board
 Nevada driller's license number issued by the 1753
 Division of Water Resource, the on-site driller

Signed Wayne V. [Signature]
 By driller performing the actual drilling on site or contract
 Date 12/5/2007

STATE ENGINEER AND GEOLOGIST
 2008 JAN -2 AM 11:45

RECEIVED