

STATE OF NEVADA  
 DIVISION OF WATER RESOURCES  
**WELL DRILLER'S PLUGGING REPORT**

OFFICE USE ONLY  
 Log No. 105341  
 Permit No. \_\_\_\_\_  
 Basin 101

**PRINT OR TYPE ONLY  
 DO NOT WRITE ON BACK**

*Please fill in this form in its entirety in  
 accordance with NRS 534.170 and NAC 534.340*

NOTICE OF INTENT NO. 60698

1. OWNER, Duffer Fairbanks  
 MAILING ADDRESS #6 Herman Lane Yerington, NV 8944  
 Yerington, NV 89447

ADDRESS AT WELL LOCATION 6999 Austin Hwy #1  
 Fallon, NV 89406

2. LOCATION NE 1/4 SW 1/4 Sec 1 T 18 R 29  
 PERMIT NO 49125 Parcel No.

Latitude 39.44901 Longitude -118.67843  WGS 84  
 Subdivision Name \_\_\_\_\_ County Churchill

3. TYPE OF WELL  
 Irrigation

Is this well being plugged because a  
 replacement well was drilled? No  
 If yes what is replacement well NOI?

Is there an existing well log? Yes  
 If yes, what is NDWR well log #? ~~64941~~ 66651

4. EXISTING WELL CONSTRUCTION  
 Depth Drilled 190 Feet Depth Cased 180 Feet

7. WELL PLUGGING PROCEDURE  
 Was well cleaned out to total depth? Yes  
 If well was not cleaned out to total depth, please explain why:

EXISTING CASING SCHEDULE

| Size O.D.<br>(inches) | Weight/Ft.<br>(Pounds) | Wall Thickness | From<br>(Feet) | To<br>(Feet) |
|-----------------------|------------------------|----------------|----------------|--------------|
| 16                    | 42.1                   | 0.250          | 0              | 180          |

Was well contaminated? No  
 Was casing pulled? No  
 Was casing overdrilled? No

Existing Perforations:

Type perforation Mill Cut  
 Size perforation 0.125  
 From 100 feet to 180 feet

If casing was left in place, please show where additional perforations were made:

Additional Perforations:

Type perforator used: Air Roller  
 From 50 To 100 Number of perfs per linear foot 16

5. WATER LEVEL

Static Water Level 11 feet below land surface  
 Artesian Flow G.P.M. P.S.I.  
 Water temperature °F Quality unknown

8. WELL PLUGGING MATERIALS

|                  |         |             |        |
|------------------|---------|-------------|--------|
| From 195 Feet to | 20 Feet | Bentonite   | Pumped |
| From 20 Feet to  | 0 Feet  | Neat Cement | Pumped |

6. Additional Notes or Comments

Pumped 74 bags of 20% Bentonite grout. Installed 1 yd of neat cement from 20 ft to surface.

N 39.449108

w 118.677456 NAD27

Neat Cement Fluid Weight 156 lbs/gal  
 Bentonite Grout 20 % Bentonite  
 Date Started 10/17/2007  
 Date Completed 11/1/2007

9. DRILLER'S CERTIFICATION

This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Parsons Drilling, Inc.  
 Contracto  
 Address 403 McLean Road  
 Fallon, NV 89407

Contracto  
 Nevada contractor's license number 29064  
 issued by the State Contractor's Board  
 Nevada driller's license number issued by the 2307  
 Division of Water Resource, the on-site driller

Signed [Signature]  
 By driller performing the actual drilling on site or contract  
 Date 12/11/2007

STATE OF NEVADA

2000 JAN 24 AM 11:43