

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 31795

1. OWNER VIDIER WATER ADDRESS AT WELL LOCATION TULE DESERT BASIN 221
 MAILING ADDRESS 3480 GS RICHARDS SUITE 101 CARSON CITY NV. 89703
 2. LOCATION NW 1/4 SE 1/4 Sec. 27 T 9 N OR 68 E LINCOLN County
 PERMIT NO. R-1395 Parcel No. N/A Subdivision Name N/A
Issued by Water Resources

3. WORK PERFORMED
 New Well Replace Recondition Deepen Abandon Other
 EXPLORATORY PROPOSED USE
 Domestic Municipal/Industrial Irrigation Monitor Test Stock Cable Rotary RVC Air Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
* SEE ATTACHED Log Depth = 3808 per LITHOLOGIC LOG				
G.P.S. 37° 7' 27N / 114° 22' 08W ELEVATION 3246'				

8. WELL CONSTRUCTION
 Depth Drilled 3730 Feet Depth Cased 3705 Feet
 HOLE DIAMETER (BIT SIZE)
 From 34 Inches To 50 Feet
 From 17 1/2 Inches To 3730 Feet
 From _____ Inches To _____ Feet

8. CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
8.625		.312	0	3200'
8.625		.312	3280	3340
8.625		.312	3560	3600

Perforations: 8.625 .312 3700 3705
 Type perforation LOUVER
 Size perforation .125
 From 3200 feet to 3280 feet
 From 3340 feet to 3560 feet
 From 3600 feet to 3700 feet
 From _____ feet to _____ feet
 From _____ feet to _____ feet

Surface Seal: Yes No Seal Type: Neat Cement Cement Grout Concrete Grout
 Depth of Seal 50'
 Placement Method: Pumped Poured
 Gravel Packed: Yes No
 From 3730 feet to 3120 feet

9. WATER LEVEL
 Static water level 600' feet below land surface
 Artesian flow N/A G.P.M. N/A P.S.I.
 Water temperature N/A °F Quality N/A

Date started 7-9, 2007
 Date completed 1-24, 2008

7. WELL TEST DATA

TEST METHOD:	Bailer	Pump	Air Lift
G.P.M.			
Draw Down (Feet Below)			
DONR/DWR RECEIVED APR 21 2008 LAS VEGAS OFFICE			

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.
 Name LAYNE CHRISTENSEN Contractor
 Address 11001 ETIWANDA AVE. FONTANA CA. 92337 Contractor
 Nevada contractor's license number issued by the State Contractor's Board 0019101
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1660
 Signed [Signature]
 By driller performing actual drilling on site or contractor
 Date 4-11-08

Log 105530

Hole ID	From	To	Lithology Keyword	Lithology Description
TMW-9	0	380	Alluvium	Sand and gravel with clay. Sands are fine to very fine grained, multi colors. Gravels are of mixed lithologies and colors. Clay is light gray. Dry.
TMW-9	380	390	Tuff	Tuff, glassy, devitrified reddish brown with clay. Soft.
TMW-9	390	440	Sandy clay	Clay with tuffaceous sand. Clay is yellow brown with dark spec's. Sand are rounded to sub-rounded grains. Soft.
TMW-9	440	500	Clayey gravel	Clayey gravel, clay is initially brick red and fades to brownish red with depth. Gravel lithics are gray limestones and pale red sandstones.
TMW-9	500	600	Gravel	Gravel, pale red sandstones and gray limestones with reddish brown clay. Clay percentage increases with depth.
TMW-9	600	730	Clayey gravel	Clayey gravel, gravel lithics are pale red sandstones and gray limestones. Buff color tuffaceous sandstone at 650-660.
TMW-9	730	1060	Gravel	Gravel, clean. Gravel lithics are light and dark gray limestones, pale red sandstones, some quartzite. Some minor reddish brown clay seams.
TMW-9	1060	1710	Clayey gravel	Clayey gravel, gravel lithics are light and dark gray as well as red limestone and pale red sandstone. Some clay seams from 1220-1230 and 1310 to 1320.
TMW-9	1710	1770	Clay	Clay. Moderate red. Acid reaction. Last 20 feet contain some gravels of gray limestone and pale red sandstones.
TMW-9	1770	2040	Clayey gravel	Clayey gravel, gravel lithics are light and dark gray as well as red limestone and pale red sandstone. Some minor clay seams.
TMW-9	2040	2060	Clay	Clay. Pale red. Acid reaction.
TMW-9	2060	2140	Clayey gravel	Clayey gravel, lithics include fine grained dark gray limestone, pale red sandstone. Minor clay lenses.
TMW-9	2140	2290	Gravel	Clayey gravel, lithics include limestone breccia, dark gray limestone, red sandstone. Minor clay lenses.
TMW-9	2290	2330	Gravel	Clayey gravel, lithics include gray dolomite and pale red sandstone. Staining on some faces, reddish brown and reddish color.
TMW-9	2330	2700	Gravel	Gravel, lithics of gray limestone, some cherty. Some pale red fine grained sandstone. Some minor clay seams.
TMW-9	2700	2740	Gravel	Gravel, lithics of medium gray to pale reddish brown sandstone. Fine grained. Some clays.
TMW-9	2740	2780	Gravel	Gravel, lithics of gray limestone. Clay is pale red. Acid reaction.
TMW-9	2780	2790	Clayey gravel	Gravel, lithics of red sandstone and gray limestone. Clay is pale red. Acid reaction.
TMW-9	2790	2880	Gravel	Gravel, lithics of medium and dark gray limestone. Clay zones from 2810 to 2830 and 2860 to 2870.

DCNR/DWR
RECEIVED
APR 21 2008
LAS VEGAS OFFICE

TMW-9	2880	2890	Clayey gravel	Gravel, lithics of red sandstone and gray limesone. Clay is red. Acid reaction.
TMW-9	2890	2930	Gravel	Gravel, lithics of gray to pale reddish brown sandstone. Fine grained. Calcium cemented. Some minor clay zones.
TMW-9	2930	3050	Gravel	Gravel, very coarse to cobbles. Gray limestone and pale red sandstones. Many are sub rounded. Frosted faces and coated sides.
TMW-9	3050	3120	Dolomite	Weathered dolomite. Very fine grained. Gray (N7) to pinkish gray (5R 8/2). Calcite veining.
TMW-9	3120	3260	Dolomite	Dolomite. Very fine grained. Gray (N7) to dark gray (N3). Abundant calcite veining. Micritic.
TMW-9	3260	3360	Brecciated limestone	Limestone. fine crystalline, dark gray (N3). Calcite veining. Arsenopyrite crystals visible. Highly fractured and brecciated, some slickensides visible.
TMW-9	3360	3385	Fault breccia	Fault. Rubble zone from 3300 through 3425. Dolomite, very fine grained, gray (N7), calcite veining, slickensides. Coarse sand and gravel, brown quartzite and gray LS, No fluid loss.
TMW-9	3385	3425	Brecciated limestone	Limestone, bedded with shale and thin sandstone layers. Fine crystals. Medium gray (N5). Calcite veining. Staining on some faces. Shaly partings, slickensides visible.
TMW-9	3425	3770	Bedded limestone	Limestone, bedded with shale and thin sandstone layers. Fine crystals. Medium gray (N5). Calcite veining. Staining on some faces. Shaly partings, slickensides visible. Some sandstone seams. Sandstones are fine to very coarse rounded grains. Colors
TMW-9	3770	3780	Sandstone	Sandstone. Medium to very fine rounded grains. Grayish pink (5R 8/2). Calcium cemented. Some gypsum crystals.
TMW-9	3780	3782	Fault breccia	Fault between sandstone and limestone. Fluid take zone.
TMW-9	3782	3808	Bedded limestone	Limestone bedded with sandstone. Fine crystalline limestone, dark gray (N3) with calcite veining and staining on some faces. Shaly partings. Gypsum crystals. Sandstones are very fine grained. Gray sandstones are calcium cemented and the olive brown (5

