



Since 1968

WAYNE PERRY, INC.

Environmental Remediation, Construction and Consulting

205  
615  
34  
139.34.813-604

Logs 105550  
105551  
105552  
105553  
105554  
105555  
105556  
105557

October 25, 1995

Mr. Richard Moles, P.E.  
Department of Conservation and Natural Resources  
Division of Water Resources, Southern Nevada Branch Office  
Mailroom Complex  
Las Vegas, Nevada 89158

**SUBJECT: TRANSMITTAL OF WELL COMPLETION INFORMATION**  
FORMER SHELL OIL COMPANY STATION (WIC #227-4880-0509)  
1021 EAST CHARLESTON BOULEVARD (at 11th Street)  
LAS VEGAS, NEVADA  
WPC PROJECT NO. 94.061

Dear Mr. Moles:

This letter provides information concerning the location and construction of 8 groundwater monitoring wells which were installed at the above referenced property on January 31 through February 2, 1995 under your Waiver No. MO-2528. I apologize for the delay in transmitting this information to your office. As these wells may become part of an ongoing groundwater monitoring program for the site, a request for extension of the waiver will be forwarded to your office in the near future.

The wells were installed by Weber Environmental, Inc., a Nevada licensed driller, in general accordance with our waiver request letter dated December 1, 1994. Although the waiver request letter indicated a proposed boring depth of 30 feet, the borings were drilled to only 15 feet due to auger refusal at this depth.

Attached is a Plot Plan showing the locations of the wells and a copy of the boring/well construction log for each of the 8 wells. Please call me if you have any questions regarding this letter.


Very truly yours,  
WAYNE PERRY, INC.

A handwritten signature in cursive script that reads "David E. Potts".

David E. Potts, P.E.



Log 105553



<b>WAYNE PERRY CONSTRUCTION</b> Buena Park, CA		<b>Log of WELL MW-5</b>	
PROJECT: Shell Oil Company		SURFACE ELEVATION:	
LOCATION: Charleston & 11th Street, Las Vegas, NV		TOTAL DEPTH: 15 ft.	DIAMETER:
PROJECT NO.: 94.061		DEPTH TO FIRST SATURATION: 10 ft.	
DATE BEGAN: 02/01/95	FINISHED: 02/01/95	WELL CASING ELEVATION: 1991.58 ft.	
DRILLING COMPANY: Weber Environmental		STATIC WATER LEVEL: 8.21 ft.	DATE: 2/23/95
DRILLING METHOD: Solid Stem Auger		LOGGED BY: Steve Beadle	

This log is a representation of subsurface conditions at the time and place of drilling. With the passage of time or at any other location, there may be consequential changes in conditions.

DEPTH (feet)	Samples	Sample I.D.	Time	Blows/6"	Geologic Description	PID (ppm)	Soil Class	Graphic Log	DEPTH (feet)	Well Diagram
					Asphalt to 2"		ac	[Pattern]		
					SAND: fine-grained, brown, dry, loose, trace silt, roots.		sp	[Pattern]		
5		B5-5	11:26	2/3/4	Clayey SILT: olive, moist, stiff, moderately plastic, dark organic material.	100	ml	[Pattern]	5	
					Silty CLAY: gray, wet, soft, locally cemented, hydrocarbon odor; saturated at 10 feet.		cl	[Pattern]		
10		B5-9	11:35	7/7/6	CALICHE: gray white, very hard, saturated.	300	caliche	[Pattern]	10	
					Silty CLAY: gray, wet, soft; trace fine- to coarse-grained sand and cemented sand fragments.		cl	[Pattern]		
15					Total depth = 15'				15	
20									20	
25									25	
30									30	

Remarks/Notes: 1) Groundwater occurred at 10 feet.  
 2) Completed as 2-inch diameter groundwater monitoring well.  
 3) Significant amounts of Caliche from 10-12 feet.