STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 105559
Permit No.
Basin 066

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 61286

1. OWNER Barrick Gold Exploration
MAILING ADDRESS 293 Spruce Road
Elko, NV 89801

ADDRESS AT WELL LOCATION 19 Miles NE of Golconda, NV
Hole #RPZ2S
Subdivision Name: County: Humboldt

2. LOCATION SE ¼ NE ¼ Sec 33 T 38N N/S R 42 E
PERMIT/WAIVER No. NEV2005102
Issued by Water Resources Parcel No.

Latitude 41.128442
Longitude 117.241986
UTM E 479687.58 [x] NAD 27
N 4552831.56 [ ] NAD 83/WGS 84

3. WORKED PERFORMED
[x] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [x] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [ ] Rotary [x] RVC
[ ] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Alluvium		0	140	140
Piezometer				
33 Bags of #8 Sand 50lb each				
2 Bags of 3/8" chips 50lb each				
18 Bags of Cement 94lb each				

Date started: 16-Jan , 20 08
Date completed: 17-Jan , 20 08

9. WELL CONSTRUCTION
Depth Drilled 140 Feet Depth Cased 138 ~~140~~ Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
8 3/4	Inches	0	Feet	20	Feet
5 7/8	Inches	20	Feet	140	Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
1	Nominal	Sch. 80	+2	138

Perforations:
Type of perforation Slotted
Size of perforation 0.02
From 58 feet to 138 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: [x] Yes [ ] No
[x] Neat Cement 0 to 50 [ ] Pumped [x] Poured
[ ] Cement Grout to [ ] Pumped [ ] Poured
[ ] Concrete Grout to [ ] Pumped [ ] Poured
[ ] ≥30% Bentonite Grout to [ ] Pumped [ ] Poured

Gravel Pack: [x] Yes [ ] No 55 to 140 [ ] Pumped [x] Poured
Type: #8 Sand
Bentonite Chips: [x] Yes [ ] No 50 to 55 [ ] Pumped [x] Poured
Type: 3/8" hole plug

7. Water Level
Static water level: Dry feet below land surface
Artesian Flow: No G.P.M. N/A P.S.I.
Water Temperature: °F
Quality:

8. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [ ] Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
N/A			

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Eklund Drilling Company, Inc. (Contractor)
Address PO Box 2748 (Contractor)
Elko, NV 89803
Nevada contractor's license number issued by the *State Contractor's Board* 0030823
Nevada driller's license number issued by the Division of Water Resources, the *on-site driller* M-2260
Signed Keese Schoul by [signature] (By driller performing actual drilling on site or contractor)
Date 1/17/2008

(Rev. 05-08)

USE ADDITIONAL SHEETS IF NECESSARY