

LK-31

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY

Log No. 105610
Permit No.
Basin 751

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in
accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 59268

1 OWNER Newmont Mining Corp. ADDRESS AT WELL LOCATION Gold Quarry Minesite, about 6 miles
MAILING ADDRESS P.O. Box 669 north of Carlin, NV
Carlin, NV 89822

2 LOCATION NW 1/4 NE 1/4 Sec 2 T 33N N/S R 51 E Latitude UTM E 567170
PERMIT/WAIVER No. 56838 Longitude N 4514870
Issued by Water Resources Parcel No.

3 TYPE OF WELL
Domestic Irrigation Test
Municipal/Industrial Monitor Stock
Is this well being plugged because a replacement well was drilled? No
Is there an existing well log? Yes 71217

4 EXISTING WELL CONSTRUCTION
Depth Drilled 320 Feet Depth Cased 320 Feet

Table with 5 columns: Size O.D. (Inches), Weight/Ft. (Pounds), Wall Thickness (Inches), From (Feet), To (Feet). Row 1: 8.625, 32, 0.3, +2, 320.

Existing Perforations:
Type of perforation Louver
Size of perforation 0.125"
From 60 feet to 320 feet

7 WELL PLUGGING PROCEDURE
Was well cleaned out to total depth? yes no
If well was not cleaned out to total depth, please explain why: Pumping equipment was pulled, and the well found to be open to original t.d.

Was the well contaminated? yes no
Was the casing pulled? yes no
Was the casing over drilled? yes no
Additional Perforations:
Type of perforator used: No additional perforations were made.

5 WATER LEVEL
Static water level 283 feet below land surface
Artesian flow
Water temperature 60 G.P.M. Quality Good

8 WELL PLUGGING MATERIALS

Table with 4 columns: From (feet), To (feet), Material Used, Status. Rows include Super Plug, Kwik Plug, Neat Cement, Clean Fill/Gravel.

6 Additional Notes or Comments
Abandonment procedure was discussed with DWR prior to performing the work. The basic procedure entails circulating the bentonite grout (Super Plug) until it will rise no further, then a bentonite chip (Kwik Plug) bridge. Neat cement is then pumped until it is 20' above the uppermost perforation in the casing. The balance of the casing is filled with clean fill or gravel, as a safety measure.

Neat Cement Fluid Weight 15 lbs/gal
Bentonite Grout 12 % bentonite
Date Started 1/9/2007
Date Completed 1/10/2007

9 DRILLER'S CERTIFICATION

This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.
Name Eklund Drilling Company, Inc.
Address PO Box 2748
Elko, NV 89803
Nevada contractor's license number 0030823
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1776
Signed Arthur Steelman
Date 3/7/2007