

LK-15

STATE OF NEVADA  
DIVISION OF WATER RESOURCES  
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY  
Log No. 105613  
Permit No. \_\_\_\_\_  
Basin 051

PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK

Please complete this form in its entirety in  
accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 59268

1 OWNER Newmont Mining Corp.  
MAILING ADDRESS P.O. Box 669  
Carlin, NV 89822

ADDRESS AT WELL LOCATION Gold Quarry Minesite, about 6 miles  
north of Carlin, NV  
Subdivision Name: \_\_\_\_\_ County: Eureka

2 LOCATION SW 1/4 NE 1/4 Sec 2 T 33N N/S R 51 E  
PERMIT/WAIVER No. 56838  
Issued by Water Resources Parcel No. \_\_\_\_\_

Latitude UTM E -567170  NAD 27  
Longitude N -4514870  NAD 83/WGS 84

3 TYPE OF WELL  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock

Is this well being plugged because a replacement well was drilled? No  
If yes, what is replacement well NOI? \_\_\_\_\_

Is there an existing well log? Yes  
64998  
If yes, what is NDWR well log #? 71458

4 EXISTING WELL CONSTRUCTION  
Depth Drilled 320 Feet Depth Cased 320 Feet

7 WELL PLUGGING PROCEDURE  
Was well cleaned out to total depth?  yes  no

EXISTING CASING SCHEDULE				
Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
8.625	32	0.3	+2	320

If well was not cleaned out to total depth, please explain why: Pumping equipment was pulled, and the well found to be open to original t.d.

Existing Perforations:

Type of perforation	Size of perforation	Louver
From <u>60</u> feet to <u>320</u> feet	<u>0.125"</u>	
From _____ feet to _____ feet		
From _____ feet to _____ feet		
From _____ feet to _____ feet		
From _____ feet to _____ feet		

Was the well contaminated?  yes  no  
Was the casing pulled?  yes  no  
Was the casing over drilled?  yes  no

If casing was left in place, please show where additional perforations were made:  
Additional Perforations:  
Type of perforator used: No additional perforations were made.

5 WATER LEVEL  
Static water level 278 feet below land surface  
Artesian flow \_\_\_\_\_ G.P.M. \_\_\_\_\_ P.S.I.  
Water temperature 60 °F Quality Good

8 WELL PLUGGING MATERIALS

6 Additional Notes or Comments  
Abandonment procedure was discussed with DWR prior to performing the work. The basic procedure entails circulating the bentonite grout (Super Plug) until it will rise no further, then a bentonite chip (Kwik Plug) bridge. Neat cement is then pumped until it is 20' above the uppermost perforation in the casing. The balance of the casing is filled with clean fill or gravel, as a safety measure.

From	feet to	Material Used	<input checked="" type="checkbox"/> Pumped	<input type="checkbox"/> Poured
From <u>400</u>	feet to <u>123</u>	feet Super Plug	<input checked="" type="checkbox"/>	<input type="checkbox"/>
From <u>123</u>	feet to <u>112</u>	feet Kwik Plug	<input type="checkbox"/>	<input checked="" type="checkbox"/>
From <u>112</u>	feet to <u>47</u>	feet Neat Cement	<input checked="" type="checkbox"/>	<input type="checkbox"/>
From <u>47</u>	feet to <u>0</u>	feet Clean Fill/Gravel	<input type="checkbox"/>	<input checked="" type="checkbox"/>
From _____	feet to _____	feet _____	<input type="checkbox"/>	<input type="checkbox"/>
From _____	feet to _____	feet _____	<input type="checkbox"/>	<input type="checkbox"/>

Neat Cement Fluid Weight 15 lbs/gal  
Bentonite Grout 12 % bentonite  
Date Started 1/11/2007  
Date Completed 1/11/2007

21-11117 6-2007/07

9 DRILLER'S CERTIFICATION  
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.  
Name Eklund Drilling Company, Inc. Contractor  
Address PO Box 2748 Contractor  
Elko, NV 89803  
Nevada contractor's license number issued by the State Contractor's Board 0030823  
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1776  
Signed Arthur Steelman  
By driller performing actual drilling on site or contractor  
Date 3/7/2007