TT22-MW02

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 105889
Permit No.
Basin 101

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 61864

1. OWNER NAS FALLON
MAILING ADDRESS ~~1580~~ 4755 S. Pasture Rd
Fallon, NV 89496

ADDRESS AT WELL LOCATION ~~1580~~ 4755 S. Pasture Rd
Fallon, NV 89496
Subdivision Name: NAS FALLON County: Churchill

2. LOCATION SE ¼ NE ¼ Sec 14 T 18 ☐N/S R 29 E
PERMIT/WAIVER No. IRP
Issued by Water Resources
Parcel No. 006-611-01

Latitude
Longitude
UTM E 2594251.46 ☒ NAD 27
N 14825973.61 ☐ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☒ Other Auger

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
SAND (CLAYEY)		0'	5'	5'
SAND		5'	15'	10'
CLAY		15'	19'	4'

N 39.426667
W 118.690056 NAD27

Date started: 4.3, 20 08
Date completed: 4.3, 20 08

7. Water Level
Static water level: 5' feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: °F
Quality:

8. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

9. WELL CONSTRUCTION
Depth Drilled 18 Feet Depth Cased 18 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
8	Inches	0	Feet	18	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2"		SCH. 40	0	18

Perforations:
Type of perforation Manufactured Slotted
Size of perforation .010
From 3 feet to 18 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: ☒ Yes ☐ No
☒ Neat Cement 0' to 1' ☐ Pumped ☒ Poured
☐ Cement Grout to ☐ Pumped ☐ Poured
☐ Concrete Grout to ☐ Pumped ☐ Poured
☐ ≥30% Bentonite Grout to ☐ Pumped ☐ Poured

Gravel Pack: ☒ Yes ☐ No 2½' to 18' ☐ Pumped ☒ Poured
Type: 2/16 Sand
Bentonite Chips: ☒ Yes ☐ No 1' to 2½' ☐ Pumped ☒ Poured
Type: 3/8 Bentonite chips

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Gregg Drilling (Contractor)
Address 950 Howe Rd (Contractor)
Martinez, CA 94553
Nevada contractor's license number issued by the State Contractor's Board C23-0038113
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M-2328
Signed (driller performing actual drilling on site or contractor)
Date 4-3-08

(Rev. 05-08)

USE ADDITIONAL SHEETS IF NECESSARY