


STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT



OFFICE USE ONLY
Log No. 105919
Permit No. _____
Basin 066

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in
accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 61311

1 OWNER Newmont Mining Corporation
MAILING ADDRESS PO Box 388
Valmy, NV 89438

ADDRESS AT WELL LOCATION Twin Creeks
Hole #TMO-30025
Subdivision Name: _____ County: Humboldt

2 LOCATION NW 1/4 NE 1/4 Sec 30 T 39N N/S R 43 E
PERMIT/WAIVER No. _____
Issued by Water Resources Parcel No. _____

Latitude 40.237664 UTM E 485956.13 NAD 27
Longitude 117.167586 N 4564941.784 NAD 83/WGS 84

3 TYPE OF WELL
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock

Is this well being plugged because a replacement well was drilled? No
If yes, what is replacement well NOI? _____

Is there an existing well log? Yes
If yes, what is NDWR well log #? 92950

4 EXISTING WELL CONSTRUCTION
Depth Drilled 685 Feet Depth Cased 685 Feet

7 WELL PLUGGING PROCEDURE
Was well cleaned out to total depth? yes no
If well was not cleaned out to total depth, please explain why: _____

EXISTING CASING SCHEDULE				
Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
<u>4</u>	<u>Nominal</u>	<u>PVC sch 80</u>	<u>0</u>	<u>680</u>

Was the well contaminated? yes no
Was the casing pulled? yes no
Was the casing over drilled? yes no

Existing Perforations:

Type of perforation	Slotted
Size of perforation	0.02
From <u>200</u> feet to <u>660</u> feet	
From _____ feet to _____ feet	
From _____ feet to _____ feet	
From _____ feet to _____ feet	
From _____ feet to _____ feet	

Additional Perforations:

Type of perforator used:	Number of perfs per linear foot
From _____ feet to _____ feet	
From _____ feet to _____ feet	
From _____ feet to _____ feet	
From _____ feet to _____ feet	
From _____ feet to _____ feet	
From _____ feet to _____ feet	

5 WATER LEVEL
Static water level 199 feet below land surface
Artesian flow No G.P.M. N/A P.S.I.
Water temperature Warm °F Quality Good

8 WELL PLUGGING MATERIALS

Material Used	From	To	Notes
Neat Cement	<u>685</u> feet	<u>0</u> feet	<input checked="" type="checkbox"/> Pumped <input type="checkbox"/> Poured
			<input type="checkbox"/> Pumped <input type="checkbox"/> Poured
			<input type="checkbox"/> Pumped <input type="checkbox"/> Poured
			<input type="checkbox"/> Pumped <input type="checkbox"/> Poured
			<input type="checkbox"/> Pumped <input type="checkbox"/> Poured
			<input type="checkbox"/> Pumped <input type="checkbox"/> Poured

6 Additional Notes or Comments
Cut monument off @ ground level. Move over hole and check Static water level - 198'
Casing will not pull out of hole. Run trimmy in to bottom and break bottom cap. Pull back 60' and start pumping cement. Pump in 320 gal. slurry then pull back 100'. Do this until above static. Pump in a total of 210 sacks cement @ 1974 gal. slurry hole full of cement.

Neat Cement Fluid Weight 15.2 lbs/gal
Bentonite Grout 30 % bentonite
Date Started 3/19/2008
Date Completed 3/20/2008

9 DRILLER'S CERTIFICATION
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.
Name Eklund Drilling Company, Inc.
Contractor
Address PO Box 2748
Contractor
Elko, NV 89803
Nevada contractor's license number issued by the State Contractor's Board 0030823
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2089
Signed Donald School
By driller performing actual drilling on site or contractor
Date 3/20/2008