

STATE OF NEVADA  
DIVISION OF WATER RESOURCES  
WELL DRILLER'S REPORT

OFFICE USE ONLY  
Log No. 1059157  
Permit No. \_\_\_\_\_  
Basin 720

PRINT OR TYPE ONLY

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 60859

1. OWNER **Pat Ewing** ADDRESS AT WELL LOCATION **9940 Eik**  
MAILING ADDRESS **PO Box 581 Adelanto, CA 92301** **Winnemucca, NV 89445**  
Subdivision Name: \_\_\_\_\_ County: **Humboldt**

2. LOCATION NW 1/4 SW 1/4 Sec 25 T35N R36E Latitude **N40°52.705** UTM E \_\_\_\_\_  NAD 27  
PERMIT/WAIVER NO. \_\_\_\_\_ **05-531-02** Longitude **W117°53.252** N \_\_\_\_\_  NAD 83/WGS 84  
*Issued by Water Resources* Parcel No. \_\_\_\_\_

3. WORK PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Other

4. PROPOSED USE  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock

5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Sand		0	4	4
Cobles / gravel		4	64	60
Boulders / cobles		64	160	96
Clay / gravel		160	175	15
Cobles		175	205	30
Boulders / gravel		205	245	40
Clay / Gravel		245	265	20
Sand / Gravel	X	265	300	35
Clay		300	305	5

9. WELL CONSTRUCTION  
Depth Drilled **305** Feet Depth Cased **305** Feet

HOLE DIAMETER (BIT SIZE)  
From \_\_\_\_\_ To \_\_\_\_\_  
**10 5/8** Inches **0** Feet **305** Feet  
Inches Feet Feet  
Inches Feet Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
<b>6 5/8</b>	<b>10</b>	<b>188</b>	<b>+1</b>	<b>20</b>
<b>6.625</b>	<b>4.06</b>	<b>.316</b>	<b>20</b>	<b>305</b>

Perforations:  
Type of perforation **Factory Cut Slots**  
Size of perforation **050**  
From **265** feet to **305** feet  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet

Annular Seal:  Yes  No

Neat Cement 0 to 50  Pumped  Poured  
 Cement Grout \_\_\_\_\_ to \_\_\_\_\_  Pumped  Poured  
 Concrete Grout \_\_\_\_\_ to \_\_\_\_\_  Pumped  Poured  
 ≥30% Bentonite Grout \_\_\_\_\_ to \_\_\_\_\_  Pumped  Poured

Gravel Pack:  Yes  No 50 to 305  Pumped  Poured  
Type: \_\_\_\_\_  
Bentonite Chips:  Yes  No \_\_\_\_\_ to \_\_\_\_\_  Pumped  Poured  
Type: \_\_\_\_\_

Date started: **January 29, 20 08**  
Date completed: **February 6, 20 08**

7. Water Level  
Static water level: **210** feet below land surface  
Artesian Flow: **N/A** G.P.M. **N/A** P.S.I.  
Water Temperature: **cool** °F  
Quality: **good**

8. WELL TEST DATA

TEST METHOD:	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailer <input checked="" type="checkbox"/> Pump <input type="checkbox"/> Air Lift	<b>20</b>	<b>15</b>
G.P.M.		

10. DRILLER'S CERTIFICATION  
This well was drilled under my supervision and the report is true to the best of my knowledge.  
Name **Fred Anderson Drilling, Inc.** (CONTRACTOR)  
Address **10760 S. Grass Valley Road** (CONTRACTOR)  
**Winnemucca, NV 89445**  
Nevada contractor's license number issued by the State Contractor's Board **021467**  
Nevada driller's license number issued by the Division of Water Resources, the on-site driller **2083**  
Signed *Fred Anderson Drilling, Inc.*  
By driller performing actual drilling on site of contractor  
Date **February 8, 2008**