WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 105969
Permit No.
Basin 044

NOTICE OF INTENT NO. 28695

1. OWNER Gateway Gold Corporation
MAILING ADDRESS 2681 E Parleys Way Suite 204
Salt Lake City Ut 84104

ADDRESS AT WELL LOCATION
from NOI (well # PLA-MW-22) RC 6-20-08

2. LOCATION NW ¼ SE ¼ Sec. 2 T. 42 N/S R. 53 E. Elko County
PERMIT NO. M/O-1980 (SW NE) Issued by Water Resources | Parcel No. | Lat 41.565319 Lat - 115.97341 WGS-84 Subdivision Name

3. WORK PERFORMED
☑ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☑ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☑ RVC
☑ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Pit Fill	No	0	15	15
Dark Gray Siltstone	No	15	20	5
Grayish Black Siltstone	No	20	25	5
Gray to Dark Gray Conglomerate	No	25	35	10
Dark Gray to Gray Siltstone	No	35	65	30
Green Gray Gritstone	No	65	70	5
Gray To Dark Gray Siltstone	No	70	80	10
Gray Siltstone or Gritstone	No	80	110	30
Light Greenish Gray Basalt	No	110	155	45
Grayish Black Siltstone	No	155	160	5
Black Siltstone	No	160	170	10
Gray to Dark Gray Siltstone	No	170	190	20
Dark Gray-Black Siltstone	Yes	190	200	10
Black Siltstone	Yes	200	245	45
Dark Gray Siltstone	Yes	245	275	30
Gray to Dark Gray Siltstone	Yes	275	330	55
Dark Gray Siltstone	Yes	330	335	5
Dark Gray to Black Siltstone	Yes	335	384	49

N41.565423
W115.972484 NAD27

Date started Jan. 16, 2008
Date completed Jan. 21, 2008

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

Primary use as Piezometer

8. WELL CONSTRUCTION
Depth Drilled 384.5 Feet Depth Cased 384.25 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
9½ Inches		0 Feet	35 Feet
6¼ Inches		35 Feet	384.5 Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2 3/8		SCH 80 PVC	+1.66	184.25
6 in X 7' Steel Protector W Pad				

Perforations:
Type perforation Factory Slotted
Size perforation .050
From 184.25 feet to 384.25 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☑ Yes ☐ No
Depth of Seal 0-179 0-10
Placement Method: ☑ Pumped ☐ Poured
Seal Type: ☑ Neat Cement ☐ Cement Grout ☐ Concrete Grout
0-179 Bentonite
Gravel Packed: ☑ Yes ☐ No
From 179 feet to 384.5 feet

9. WATER LEVEL
Static water level 275.6 feet below land surface
Artesian flow NA G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Layne Christensen Company (Contractor)
Address 4490 West 1707 South (Contractor)
Salt Lake City Ut. 84104
Nevada contractor's license number issued by the State Contractor's Board 0019101
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1970
Signed Wilburn L. Franklin (By driller performing actual drilling on site or contractor)
Date January 30, 2008

(Rev. 12-01) USE ADDITIONAL SHEETS IF NECESSARY (O)-627