STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY
Log No. 1060025
Permit No.
Basin 066

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 61292

1 OWNER Barrick Gold Exploration
MAILING ADDRESS 293 Spruce Road
Elko, NV 89801

ADDRESS AT WELL LOCATION 19 Miles NE of Golconda, NV
Hole #RMW2NE
Subdivision Name: *County:* Humboldt

2 LOCATION SW ¼ NW ¼ Sec 34 T 38N N/S R 42 E
PERMIT/WAIVER No. NEV2005102 *Issued by Water Resources* *Parcel No.*

Latitude 41.128467
Longitude 117.237143
UTM E 480094.12
N 4552833.29
[x] NAD 27
[ ] NAD 83/WGS 84

3 TYPE OF WELL
[ ] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [x] Monitor [ ] Stock

Is this well being plugged because a replacement well was drilled? Yes
If yes, what is replacement well NOI? 61293

Is there an existing well log? ~~Yes~~
If yes, what is NDWR well log #?

4 *EXISTING WELL CONSTRUCTION*
Depth Drilled 240 Feet Depth Cased 220 Feet

EXISTING CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
1	Nominal	Sch. 80	+2	218

Existing Perforations:
Type of perforation Slotted
Size of perforation 0.02

From	188	feet to	218	feet
From		feet to		feet
From		feet to		feet
From		feet to		feet
From		feet to		feet

5 *WATER LEVEL*
Static water level 105 feet below land surface
Artesian flow No G.P.M. N/A P.S.I
Water temperature Cool °F Quality Dirty

6 Additional Notes or Comments
Drill up PVC & all materials pump abandonite from 240 ft. up to top. Pour 20' cement plug.

31 Bags of Super plug 50 lb. each
10 Bags of cement 94 lb. each

7 WELL PLUGGING PROCEDURE
Was well cleaned out to total depth? [x] yes [ ] no
If well was not cleaned out to total depth, please explain why:

Was the well contaminated? [x] yes [ ] no
Was the casing pulled? [ ] yes [x] no
Was the casing over drilled? [x] yes [ ] no
If casing was left in place, please show where additional perforations were made:
Additional Perforations:
Type of perforater used:

From		feet to		feet	Number of perfs per linear foot
From		feet to		feet	Number of perfs per linear foot
From		feet to		feet	Number of perfs per linear foot
From		feet to		feet	Number of perfs per linear foot
From		feet to		feet	Number of perfs per linear foot
From		feet to		feet	Number of perfs per linear foot

8 WELL PLUGGING MATERIALS

					Material Used		
From	20	feet to	240	feet	abandonite	[x] Pumped	[ ] Poured
From	0	feet to	20	feet	cement	[ ] Pumped	[x] Poured
From		feet to		feet		[ ] Pumped	[ ] Poured
From		feet to		feet		[ ] Pumped	[ ] Poured
From		feet to		feet		[ ] Pumped	[ ] Poured
From		feet to		feet		[ ] Pumped	[ ] Poured

Neat Cement Fluid Weight 27.4 lbs/gal
Bentonite Grout 12 % bentonite

Date Started 1/29/2008
Date Completed 1/30/2008

9 DRILLER'S CERTIFICATION
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.

Name Eklund Drilling Company, Inc. (Contractor)
Address PO Box 2748 (Contractor)
Elko, NV 89803
Nevada contractor's license number issued by the *State Contractor's Board* 0030823
Nevada driller's license number issued by the Division of Water Resources, the *on-site driller* M-2260
Signed Reese Schorl by [illegible] (By driller performing actual drilling on site or contractor)
Date 2/22/2008

(Rev. 05-06)

USE ADDITIONAL SHEETS IF NECESSARY