

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY

Log No. 106077
Permit No. _____
Basin 666

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in
accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 61313

1 OWNER Newmont Mining Corp.
MAILING ADDRESS PO Box 669
NE Carlin, NV 89822

ADDRESS AT WELL LOCATION Twin Creeks Mine
Hole #TWD-00039
Subdivision Name: _____ County: Humboldt

2 LOCATION NW 1/4 NE 1/4 Sec 30 T 39N N/S R 43 E
PERMIT/WAIVER No. SE 60051
Issued by Water Resources Parcel No.

Latitude 41.230406 UTM E 486391.055 NAD 27
Longitude 117.162378 N 4564135.2401 NAD 83/WGS 84

3 TYPE OF WELL
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock

Is this well being plugged because a replacement well was drilled? No
If yes, what is replacement well NO? _____

Is there an existing well log? Yes
72944
If yes, what is NDWR well log #? 22941

4 EXISTING WELL CONSTRUCTION
Depth Drilled 802.5 Feet Depth Cased 802.5 Feet

7 WELL PLUGGING PROCEDURE
Was well cleaned out to total depth? yes no
If well was not cleaned out to total depth, please explain why: _____

EXISTING CASING SCHEDULE				
Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
24	63.41	.25	0	17
16	42.05	.25	+1	802.5

Was the well contaminated? yes no
Was the casing pulled? yes no
Was the casing over drilled? yes no
If casing was left in place, please show where additional perforations were made: _____

Existing Perforations:				
Type of perforation	Size of perforation	Slotted	From	To
		0.125		
From	97	feet to	499	feet
From	539	feet to	781	feet
From		feet to		feet
From		feet to		feet
From		feet to		feet

Additional Perforations:
Type of perforator used:
From _____ feet to _____ feet Number of perfs per linear foot _____
From _____ feet to _____ feet Number of perfs per linear foot _____
From _____ feet to _____ feet Number of perfs per linear foot _____
From _____ feet to _____ feet Number of perfs per linear foot _____
From _____ feet to _____ feet Number of perfs per linear foot _____
From _____ feet to _____ feet Number of perfs per linear foot _____

5 WATER LEVEL
Static water level 199.5 feet below land surface
Artesian flow No G.P.M. N/A P.S.I.
Water temperature Warm ° F Quality Good

8 WELL PLUGGING MATERIALS
Material Used
From 802.5 feet to 139 feet Bentonite Grout Pumped Poured
From 139 feet to 35 feet 3/8" Hole Plug Pumped Poured
From 35 feet to 0 feet Neat Cement Pumped Poured
From _____ feet to _____ feet _____ Pumped Poured
From _____ feet to _____ feet _____ Pumped Poured
From _____ feet to _____ feet _____ Pumped Poured

6 Additional Notes or Comments
Trip into bottom of well 802' and make sure it was clean.
Gave Joseph 24 hour notice prior to starting on 3/11.
Run 16" perforator in and perforate well from 50' down to 300' perforating even the screened areas of well. Get permitting from Tim Hunt that I did not have to re-perforate perforated areas of well so we perforated from 499 to 539 and 781 to 802 and started pumping bentonite grout from 800' up to 140'.
396 Sacks bentonite grout (super plug) 18,216 gal of slurry
Fluid level out 60' above static water level. Pour in 2 super sacks 3/8" hole plug then mix up 40 sacks of cement 376 gal of slurry and pour in aprox. 35 plug.

Neat Cement Fluid Weight 15.2 lbs/gal
Bentonite Grout 30 % bentonite
Date Started 3/12/2008
Date Completed 3/18/2008

9 DRILLER'S CERTIFICATION
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.
Name Eklund Drilling Company, Inc. Contractor
Address PO Box 2748 Contractor
Elko, NV 89803
Nevada contractor's license number issued by the State Contractor's Board 0030823
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2089
Signed Donald Schoorl By driller performing actual drilling on site or contractor
Date 4/9/2008