

STATE OF NEVADA  
 DIVISION OF WATER RESOURCES  
**WELL DRILLER'S PLUGGING REPORT**

OFFICE USE ONLY

Log No. 106209  
 Permit No. \_\_\_\_\_  
 Basin 101

NOTICE OF INTENT NO. 62301

PRINT OR TYPE ONLY  
 DO NOT WRITE ON BACK

*Please fill in this form in its entirety in  
 accordance with NRS 534.170 and NAC 534.340*

1. OWNER A & K Earthmovers Inc  
 MAILING ADDRESS P.o. Box 1059 Fallon, NV 89407  
 Fallon, NV 89407

ADDRESS AT WELL LOCATION 2020 Reno Hwy  
 Fallon, NV 89407

2. LOCATION SE 1/4 SE 1/4 Sec 26 T 19 R 28  
 PERMIT NO 63849 Parcel No. 008-361-44

Latitude 39.47772 Longitude -118.8012  WGS 84  
 Subdivision Name \_\_\_\_\_ County Churchill

3. TYPE OF WELL  
 Municipal/Industrial

Is this well being plugged because a replacement well was drilled? No  
 If yes what is replacement well NOI?

Is there an existing well log? Yes  
 If yes, what is NDWR well log #? 98290

4. EXISTING WELL CONSTRUCTION  
 Depth Drilled 165 Feet Depth Cased 165 Feet

**EXISTING CASING SCHEDULE**

Size O.D. (inches)	Weight/Ft. (Pounds)	Wall Thickness	From (Feet)	To (Feet)
8.625	14.96	0.188	0	20
8	5.82	0.258	20	165

Existing Perforations:

Type perforation Saw Cut  
 Size perforation 0.125  
 From 158 feet to 165 feet

7. WELL PLUGGING PROCEDURE  
 Was well cleaned out to total depth? Yes  
 If well was not cleaned out to total depth, please explain why:

Was well contaminated? No  
 Was casing pulled? No  
 Was casing overdrilled? No

If casing was left in place, please show where additional perforations were made:

*Additional Perforations:*

Type perforator used: Air Roller  
 From 100 To 150 Number of perfs per linear foot 12

**5. WATER LEVEL**

Static Water Level 38 feet below land surface  
 Artesian Flow G.P.M. P.S.I.  
 Water temperature ° F Quality unknown

**8. WELL PLUGGING MATERIALS**

Material  
 From 165 Feet to 20 Feet Bentonite Pumped  
 From 20 Feet to 0 Feet Neat Cement Pumped

**6. Additional Notes or Comments**

Pumped 28 bags of 20 % Bentonite Grout from 165 ft to 20 ft. Pumped 8 bags of neat cement from 20 ft to top of well.

N 39.477820  
 W 118.800233 NAD27

Neat Cement Fluid Weight 156 lbs/gal  
 Bentonite Grout 20 % Bentonite  
 Date Started 3/13/2008  
 Date Completed 3/13/2008

9. DRILLER'S CERTIFICATION  
 This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Parsons Drilling, Inc.  
 Contracto  
 Address 403 McLean Road  
 Fallon, NV 89407  
 Contracto  
 Nevada contractor's license number 29064  
 issued by the State Contractor's Board  
 Nevada driller's license number issued by the 1758  
 Division of Water Resource, the on-site driller  
 Signed [Signature]  
 By driller performing the actual drilling on site or contract  
 Date 4/3/2008

RECEIVED  
 2008 JUN 20 AM 11:42  
 STATE ENGINEERS OFFICE