STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 1062226
Permit No.
Basin 103

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 60247

1. OWNER Vidler M-W-2
MAILING ADDRESS 3480 GS Richards BLVD
Carson City, Nv 89703

ADDRESS AT WELL LOCATION Hells Bells
Carson City
Subdivision Name: County: Carson City

2. LOCATION SE ¼ NW ¼ Sec 14 T 15N N/S R 20 E
PERMIT/WAIVER No. M/O - 1493A 10-587-17
Issued by Water Resources Parcel No.

Latitude 39.16807'N
Longitude 119.70609'W
UTM E N
☐ NAD 27 ☒ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☒ Other mud

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
sand & clay		0	9	9
gravel		9	17	8
clay		17	22	5
gravel		22	30	8
clay		30	37	7
gravel		37	51	14
hard rock		51	56	5
clay & fimmes		56	73	17
hard rock		73	96	23
clay		96	105	9
rock		105	122	17
clay		122	131	9
rock		131	135	4
pumped bentonite grout		37	135	98
N 39.168173				
W 119.705092 NAD27				

Date started: 8-Apr , 20 08
Date completed: 14-Apr , 20 08

9. WELL CONSTRUCTION
Depth Drilled 135 Feet Depth Cased 37 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
9 7/8	Inches	0	Feet	135	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4	2.82	sch 40	+3	37

Perforations:
Type of perforation screen
Size of perforation 0.04
From 27 feet to 37 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: ☒ Yes ☐ No
☒ Neat Cement 0 to 5 ☒ Pumped ☐ Poured
☐ Cement Grout to ☐ Pumped ☐ Poured
☐ Concrete Grout to ☐ Pumped ☐ Poured
☒ ≥30% Bentonite Grout 5 to 25 ☒ Pumped ☐ Poured
Gravel Pack: ☒ Yes ☐ No 25 to 37 ☒ Pumped ☐ Poured
Type: sand
Bentonite Chips: ☐ Yes ☐ No to ☐ Pumped ☐ Poured
Type:

7. Water Level
Static water level: 13 feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: cool °F
Quality:

8. WELL TEST DATA
TEST METHOD: ☐ Bailer ☒ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
8	23	2

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name McKay Drilling, Inc
Contractor
Address 4850 Joule St. Suite A5
Contractor
Reno, NV 89502
Nevada contractor's license number issued by the *State Contractor's Board* 14170
Nevada driller's license number issued by the Division of Water Resources, the *on-site driller* 2121
Signed
By driller performing actual drilling on site or contractor
Date 2/13/2008

(Rev. 05-06)

USE ADDITIONAL SHEETS IF NECESSARY