STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 106442
Permit No.
Basin 071

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 60224

1. OWNER Mike Sage
MAILING ADDRESS 4200 MASIONA #89 Wmca, NV 89445
ADDRESS AT WELL LOCATION 3095 Potbelly Rd Wmca, NV 89445
Subdivision Name: County: Humboldt

2. LOCATION W ½ NE ¼ Sec 25 T 35 N/S R 37 E
PERMIT/WAIVER No. 14-142-10 *Issued by Water Resources* Parcel No.
Latitude 40.883146 Longitude 117.760630
UTM E 435915 N 4525852 ☒ NAD 27 ☐ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Replace ☐ Recondition ☐ Deepen ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test ☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC ☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Top Soil		0	2	2
Rocks Little clay		2	20	18
Gravel + Rocks		20	40	20
Sand + Gravel		40	50	10
Brown Clay		50	60	10
Sand + Gravel		60	100	40
Rocks + Gravel		100	120	20
Brown Rocky Clay		120	140	20
Gravel + Rocks		140	160	20
Sand + Gravel		160	185	25

Date started: 5-20, 2008
Date completed: 5-20, 2008

7. Water Level
Static water level: 118 Ft. feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: Cold °F
Quality: Good

8. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
Rotary	40+	UNK	2 Hrs

9. WELL CONSTRUCTION
Depth Drilled 185 Feet Depth Cased 185 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
10 5/8 Inches		0 Feet	185 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8		183	+1	185

Perforations:
Type of perforation Torch cut.
Size of perforation 5/16 x 6
From 145 feet to 185 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: ☒ Yes ☐ No

☐ Neat Cement	to		☐ Pumped	☐ Poured
☒ Cement Grout	5 to 55		☐ Pumped	☒ Poured
☐ Concrete Grout	to		☐ Pumped	☐ Poured
☐ ≥80% Bentonite Grout	to		☐ Pumped	☐ Poured

Gravel Pack: ☒ Yes ☐ No 120 to 185 ☐ Pumped ☒ Poured
Type:
Bentonite Chips: ☒ Yes ☐ No 55 to 120 ☐ Pumped ☒ Poured
Type:

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name L B J Drilling Co. (Contractor)
Address P.O. Box 902 Wmca NV 89446 (Contractor)
Nevada contractor's license number issued by the *State Contractor's Board* 9605A
Nevada driller's license number issued by the Division of Water Resources, the *on-site driller* 1807
Signed (By driller performing actual drilling on site or contractor)
Date 5-29-08

(Rev 06-08)

USE ADDITIONAL SHEETS IF NECESSARY