STATE OF NEVADA
DIVISION OF WATER RESOURCES
# WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY
Log No. 106511
Permit No.
Basin 131

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

*Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340*

NOTICE OF INTENT NO. 61339

1 OWNER Newmont Mining Corporation
MAILING ADDRESS PO Box 388
Valmy, NV 89438

ADDRESS AT WELL LOCATION Phoenix Mine - PW-5
*Subdivision Name:* *County:* Lander

2 LOCATION SW ¼ SE ¼ Sec 27 T 31N N/S R 43 E
PERMIT/WAIVER No. W-408
*Issued by Water Resources* *Parcel No.*

Latitude 40.52699
Longitude 117.11485
UTM E 375500
N 2103600
[x] NAD 27
[ ] NAD 83/WGS 84

3 TYPE OF WELL
[ ] Domestic [ ] Irrigation [ ] Test
[x] Municipal/Industrial [ ] Monitor [ ] Stock

Is this well being plugged because a replacement well was drilled? No
If yes, what is replacement well NOI?

Is there an existing well log? Yes
If yes, what is NDWR well log #? 46415

4 *EXISTING WELL CONSTRUCTION*
Depth Drilled 460 Feet Depth Cased 460 Feet

*EXISTING CASING SCHEDULE*

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|---|---|---|---|---|
| 6 | | .188 | 0 | 460 |
| | | | | |
| | | | | |
| | | | | |

*Existing Perforations:*
Type of perforation Mill Slot
Size of perforation 0.125

| | | | | |
|---|---|---|---|---|
| From | 250 | feet to | 460 | feet |
| From | | feet to | | feet |
| From | | feet to | | feet |
| From | | feet to | | feet |
| From | | feet to | | feet |

5 *WATER LEVEL*
*Static water level* 315 feet below land surface
Artesian flow No G.P.M. N/A P.S.I
Water temperature N/A °F Quality

6 Additional Notes or Comments

Run perforator from 50' to 450' with 4 vertical rows.

Pump abandonment slurry through drill pipe until circulated. Tripped pipe out to 100'. Filled, tripped out and set surface plug to 25'. Used 45 sacks of super plug and used 5 sacks (94 lb) of cement.

7 WELL PLUGGING PROCEDURE
Was well cleaned out to total depth? [x] yes [ ] no
If well was not cleaned out to total depth, please explain why:

Was the well contaminated? [ ] yes [x] no
Was the casing pulled? [ ] yes [x] no
Was the casing over drilled? [ ] yes [x] no
If casing was left in place, please show where additional perforations were made:

*Additional Perforations:*
Type of perforater used: Star Wheel

| | | | | | |
|---|---|---|---|---|---|
| From | 50 | feet to | 450 | feet | Number of perfs per linear foot App. 8 |
| From | | feet to | | feet | Number of perfs per linear foot |
| From | | feet to | | feet | Number of perfs per linear foot |
| From | | feet to | | feet | Number of perfs per linear foot |
| From | | feet to | | feet | Number of perfs per linear foot |
| From | | feet to | | feet | Number of perfs per linear foot |

8 WELL PLUGGING MATERIALS

| | | | | | Material Used | | |
|---|---|---|---|---|---|---|---|
| From | 440 | feet to | 0 | feet | Super Plug | [x] Pumped | [ ] Poured |
| From | 25 | feet to | 0 | feet | Cement | [ ] Pumped | [x] Poured |
| From | | feet to | | feet | | [ ] Pumped | [ ] Poured |
| From | | feet to | | feet | | [ ] Pumped | [ ] Poured |
| From | | feet to | | feet | | [ ] Pumped | [ ] Poured |
| From | | feet to | | feet | | [ ] Pumped | [ ] Poured |

Neat Cement Fluid Weight 16.2 lbs/gal
Bentonite Grout 12.5 % bentonite

Date Started 4/8/2008
Date Completed 4/9/2008

9 DRILLER'S CERTIFICATION
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.

Name Eklund Drilling Company, Inc.
Contractor
Address PO Box 2748
Contractor
Elko, NV 89803
Nevada contractor's license number issued by the *State Contractor's Board* 0030823
Nevada driller's license number issued by the Division of Water Resources, the *on-site driller* M-1769

Signed Warren Hartley by (MH)
By driller performing actual drilling on site or contractor
Date 4/30/2008

(Rev. 05-06)

USE ADDITIONAL SHEETS IF NECESSARY